	SUPP		INFORMATION SUPPLIER SIGNA	TURE				
SUPPL		HashiCorp, Inc.		IONE				
SUPPL	IER CONTACT EMAIL	• *	Dhyaneshwari chandarana (Mar 21, 2025 21:26	 GMT+5.5)				
	ACCREDITED L		ACCREDITED LABORATOR					
LABO	RATORY NAME	UNH InterOperability Laboratory	Michayla Newcombe					
LABO	RATORY CONTACT EMAIL	usgv6-sdoc@iol.unh.edu	Michayla Newcombe (Mar 21, 2025 13:00 EDT)	_				
	[2] PRODUCT VE	RSION TESTED	[3] PRODUCT I	D				
	Vault	1.19.0	Hashicorp	Vault				
	APPLICABLE SER	IES HARDWARE	APPLICABLE SERIES S	OFTWARE				
			COMPOSITE SDOC					
🖌 Ur	itary: All of the declared ca	apabilities of this product are	Composite: Some or all of the capa	bilities of this product				
	ssed by original test results		are provided by the use and/or integratic components that have their own unique relevant referenced SDoCs are identifie linked.	on of unmodified SDoCs. All of the				
[6] REF	SUPPLIER	PRODUCT ID/STACK ID	CAPABILITY SUMMARY	COMPOSITE SDOC LINK				
i.	HashiCorp, Inc.	l	JSGv6-r1:App-Serv+IPv6-On					
				-				
		[7] USGV6-CAPAB	LE REQUIREMENTS					
	SGv6-r1-Capable-Host			6-r1-Capable-NPP				
) REFERENCED					
i. ii.	NIST SP 500-267Br1, U	ISGv6 Profile						
11.		[9] SUPPLEMENTA	ARY ATTESTATIONS					
That is	[9] SUPPLEMENTARY ATTESTATIONS This product is fully functional in dual stack environments. That is, no claimed capabilities are invalidated if this product is operated in a dual stack (IPv6 and IPv4) network environment. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.							
unique covere	nis SDoC contains a capabi e IPv6 stack in the product. ed are documented, and ho hose reported are explained	If not, the stacks/ports not w their IPv6 capabilities differ	All of the products listed in the product implemented such that their capabilities function across the entire product family. conformance and interoperability test rest of an identified member of this product fa SDoC. The SDoC attests that these test identical and unmodified for all the product	are identical in form and The specific sults for the capabilities amily are provided in this ed capabilities are				

Host Capabilities

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY
[11] SUPPORTED	CAPABILITY	CONFOR		INTEROPERABILI		NOTES
CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F		
-	Core	Core_R1v1.*_C		Core_R1v1.*_I		
-	Extended-ICMP	Self-Test		Self-Test		
-	PLPMTUD	Self-Test		Self-Test		
-	ND-Ext	Self-Test		Self-Test		
-	ND-WL	Self-Test		Self-Test		
-	SEND	Self-Test		Self-Test		
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I		
-	PriAddr	Self-Test		Self-Test		
-	DHCP- Stateless	DHCP- Stateless_R1v1 .*_C		DHCP- Stateless_R1v1 _*_I		
-	DHCP-Client	DHCP- Client_R1v1.*_C		DHCP- Client_R1v1.*_I		
-	DHCP-Client- Ext	Self-Test		Self-Test		
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I		
-	DHCP-Prefix- Ext	Self-Test		Self-Test		
-	6Lo	Self-Test		Self-Test		

Host Capabilities

		Self-Test	Self-Test		
-	Happy-Eyeballs	Sen-rest	- Sen-Test		
-	Addr-Arch	Addr- Arch_R1v1.*_C	Addr- Arch_R1v1.*_I		
-	CGA	Self-Test	Self-Test		
-	DNS-Client	Self-Test	Self-Test		
-	URI	Self-Test	Self-Test		
-	NTP-Client	Self-Test	Self-Test		
-	NTP-Server	Self-Test	Self-Test		
-	DNS-Server	Self-Test	Self-Test		
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I		
-	DHCP-Server- Ext	Self-Test	Self-Test		
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I		
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I		
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I		
-	SSHV2	Self-Test	Self-Test		
-	TLS	Self-Test	Self-Test		
-	TLS-1.3	Self-Test	Self-Test		
-	Tunneling-IP	Self-Test	Self-Test		

Host Capabilities

		Self-Test	Self-Test		
-	Tunneling-UDP				
-	XLAT	Self-Test	Self-Test		
-	NAT64	Self-Test	Self-Test		
-	DNS64	Self-Test	Self-Test		
-	SNMP	Self-Test	Self-Test		
-	Tunneling	Self-Test	Self-Test		
-	DiffServ	Self-Test	Self-Test		
-	NETCONF	Self-Test	Self-Test		
-	SSM	Self-Test	Self-Test		
-	Multicast	Multicast_R1v1 .*_C	Multicast_R1v1 .*_I		
-	ECN	Self-Test	Self-Test		
-	Link =	Self-Test	Self-Test		

Router Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY				
[11] SUPPORTED		CONFOR	MANCE RESULT ID	INTEROPERABIL TEST	ITY/FUNCTIONAL RESULT ID	NOTES			
CAPABILITY	CAPABILITY	SELECTION	RESULTID	SELECTION	RESULTID				
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F					
-	Core	Core_R1v1.*_C		Core_R1v1.*_I					
-	Extended-ICMP	Self-Test		Self-Test					
-	PLPMTUD	Self-Test		Self-Test					
-	ND-Ext	Self-Test		Self-Test					
-	ND-WL	Self-Test		Self-Test					
-	SEND	Self-Test		Self-Test					
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I					
-	PrivAddr	Self-Test		Self-Test					
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I					
-	DHCP-Prefix- Ext	Self-Test		Self-Test					
-	6Lo	Self-Test		Self-Test					
-	Addr-Arch	Addr- Arch_R1v1.*_C		Addr- Arch_R1v1.*_I					
-	CGA	Self-Test		Self-Test					

Router Capabilities

			0. If T		
-	DNS-Client	Self-Test	Self-Test		
-	URI	Self-Test	Self-Test		
-	NTP-Client	Self-Test	Self-Test		
-	NTP-Server	Self-Test	Self-Test		
-	DNS-Server	Self-Test	Self-Test		
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_		
-	DHCP-Server- Ext	Self-Test	Self-Test		
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_		
-	OSPF	Self-Test	OSPF_R1v1.*_		
-	OSPF-IPsec	Self-Test	Self-Test		
-	OSPF-Auth	Self-Test	OSPF- Auth_R1v1.*_I	,	
-	OSPF-Ext	Self-Test	Self-Test		
-	OSPF-Trans	Self-Test	Self-Test		
-	OSPF-Graceful	Self-Test	Self-Test		
-	ISIS	Self-Test	Self-Test		
-	IS-IS-Auth	Self-Test	Self-Test		
-	IS-IS-Ext	Self-Test	Self-Test		
-	IS-IS-MT	Self-Test	Self-Test		

		Self-Test	BGP_R1v1.*_I	
-	BGP			
-	BGP-Reflect	Self-Test	Self-Test	
-	BGP-Graceful	Self-Test	Self-Test	
-	BGP-FlowSpec	Self-Test	Self-Test	
-	BGP-OV	Self-Test	Self-Test	
-	BGP-VPLS	Self-Test	Self-Test	
-	BGP-EVPN	Self-Test	Self-Test	
-	BGP-6VPE	Self-Test	Self-Test	
-	BGP-MVPN	Self-Test	Self-Test	
-	MPLS	Self-Test	Self-Test	
-	CE-Router	CE_Router_R1v 1.*_C	CE_Router_R1v 1.*_I	
-	VRRP	Self-Test	Self-Test	
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I	
-	IPsec-VPN	IPsec- VPN_R1v1.*_C	IPsec- VPN_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I	
-	IPsec-SHA-512- VPN	IPsec-SHA-512- VPN_R1v1.*_C	IPsec-SHA-512- VPN_R1v1.*_I	
-	SSHV2	Self-Test	Self-Test	
-	TLS	Self-Test	Self-Test	

	1			
-	TLS-1.3	Self-Test	Self-Test	
-	Tunneling-IP	Self-Test	Self-Test	
-	Tunneling-UDP	Self-Test	Self-Test	
-	GRE	Self-Test	Self-Test	
-	DS-Lite	Self-Test	Self-Test	
-	LW4over6	Self-Test	Self-Test	
-	MAP-E	Self-Test	Self-Test	
-	MAP-T	Self-Test	Self-Test	
-	XLAT	Self-Test	Self-Test	
-	NAT64	Self-Test	Self-Test	
-	DNS64	Self-Test	Self-Test	
-	6PE	Self-Test	Self-Test	
-	LISP	Self-Test	Self-Test	
-	SNMP	Self-Test	Self-Test	
-	Tunneling	Self-Test	Self-Test	
-	DiffServ	Self-Test	Self-Test	
-	NETCONF	Self-Test	Self-Test	
-	SSM	Self-Test	Self-Test	

Router Capabilities

-	PIM-SM	Self-Test	Self-Test	
-	PIM-SM-IPsec	Self-Test	Self-Test	
-	PIM-SM-BiDir	Self-Test	Self-Test	
-	Multicast	Multicast_R1v1. *_C	Multicast_R1v1. *_I	
-	ECN	Self-Test	Self-Test	
-	Link =	Self-Test	Self-Test	

Application Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
Н	lashicorp	Vault/Va	ault 1.19.	0	USGv6-r1:App-Serv+IPv6-Only		
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFO TEST SELECTION	RMANCE RESULT ID	TEST SELECTION	LITY/FUNCTIONAL RESULT ID	NOTES	
PASS	IPv6-ONLY			IPv6- ONLY_R1v1.*_F	UNH-IOL/39600		
-	App-Serv=			APP- ONLY_R1v1.*_F			
-	Link =			Self-Test			

NPP Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILI	TY/FUNCTIONAL	NOTES	
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	FW	FW_R1v1.*_C					
-	APFW	Self-Test					
-	IDS	FW_R1v1.*_C					
-	IPS	FW_R1v1.*_C					
-	Link =	Self-Test					

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILIT	Y/FUNCTIONAL			
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	NOTES		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	DHCPv6-Guard	Self-Test		Self-Test				
-	RA-Guard	Self-Test		Self-Test				
-	MLD-Snooping	Self-Test		Self-Test				
-	Link =	Self-Test		Self-Test				

1	CONTACT INFORMATION	Supplier name, email and signature (digital recommended). Include printed name and date if wet ink signed. Accredited laboratory name, email and signature (digital recommended). Include printed name and date if wet ink signed.
2	PRODUCT VERSION TESTED	Firmware/ software version of product declared
3	PRODUCT ID	Suppliers concise name for product declared
4	PRODUCT FAMILY	Applicable hardware or software with an unmodified IPv6 stack from "PRODUCT VERSION TESTED"
5	UNITARY OR COMPOSITE	Indicate if this is a unitary or composite SDoC. If composite is checked, composite SDoC must be linked in section 6.
6	REF	Reference number to profile(s) reference in this SDoC
	SUPPLIER	Supplier name
	PRODUCT ID/STACK ID	Product ID must match field 3. As there may be more than one unique IPv6 stack, stack ID identifies particular stack described in CAPABILITY SUMMARY. Each unique stack requires a CAPABILTY SUMMARY.
	CAPABILITY SUMMARY	The strong notation as described in NIST-SP-500-267Ar1 that describes the product capabilities of the given stack.
	COMPOSITE SDOC LINK	URL link to composite SDoC referenced.
7	USGV6-CAPABLE REQUIREMENTS	Refer to section 5 in NIST-SP-500-267Br1 for CSS strings referenced in this section. Check the appropriate box if the product meets the requirements.
8	PROFILE(S) REFERENCED	Profile(s) referenced in the SDoC.
9	SUPPLEMENTARY ATTESTATIONS	Attestations made by the supplier. Check all that apply.
10	PRODUCT ID/STACK ID	PRODUCT ID/STACK ID for stack documented on given page.
	CAPABILITY SUMMARY	CAPABILITY SUMMARY for stack documented on given page.
11	SUPPORTED CAPABILITY	"PASS" – All requirements of the capability have been met
		"NOTES" – See notes for details regarding the level of support for this capability
		"X" – Capability not supported
		BLANK – No declaration for this capability
	CAPABILITY	IPv6 Capability as described in NIST-SP-500-267Ar1.
	TEST SELECTION	Test Selection Tables version of capabilities with existing test programs. Capabilities without an existing test program are indicated with "Self-Test"
	RESULT ID	Abbreviation of accredited laboratory and unique identifier of test result. Capabilities with "Self-Test" can be self-declared writing "Self Declaration" in the cell.
	NOTES	The cell must be filled out if "NOTE" is indicated for SUPPORTED CAPABILITY. Suppliers may use notes to clarify unsupported features or non-passing results.

SUPPLIER GENERAL NOTES