Suppl	iers Decla	ration of Conformity	for USGv6	Products			20	USGv6-	v1 SDOC-v1.10 Page 1		
1_		ument Requiring Co.						USGv6 Profile Version 1.0, July 2	2008. (NIST SP500-267)		
2	Product Identifier: Windows Phone										
3	Supplier's Name, Address and SDOC Contact Details										
Micros	oft Corpora										
4	Product	as Tested/Declared:	Product Idea	ntifier, vers	ion/revision information	details of d	configuratio	n tested.			
					Windows				ii		
5	Product	Family (other product	s using sam	e IPv6 star	ck(s) to which these res	uits are dec	lared to ap	ply). Check Product Family attestat	tion below.		
6	USGv6 C	apability summary.). e.g. example-prod-i	<u>id/stack-1: U</u>	stinct IPv6	Host: IPv6-Base+Addr-A	ovide a sum	mary of its	USGv6 capabilities below and includ	e a detailed test result		
7 YES	All of the de	tained or Composite clared USGv6 capabilities o	SDOC? (Mi		Some or all of the USGv6 of	apabilities of t	his product an	e provided by the use and/or integration of umo	pdified components that have		
8	SDOC			their own unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate which capabilities are provided by specific referenced components (product-id/stack-id). (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).							
		ent Supplier		Product		Stack ID:			osne products).		
[1]	- Compons	aut oabbuei		FIOGUCE	D	Stack ID:		Notes:			
[2]				 							
[3]						+					
[4]		-				+					
9	Supplem	entary Attestations (Answer all).	exile i	a politica in the state				HERZENHOE AND		
	YES	This product is fully function capabilities are invalidated 4) network environment.			YES	This product are invalidate support lpv4	t is fully functional in IPv6 only environments. T ted if this product is deployed in a network envi 4.	That is, no claimed capabilities ironment that does not			
	YES	product. If not, the stacks/ capabilities differ from tho	e capabilities test report for each unique IPv6 stack in the cks/ports not covered are documented, and how their ipv6 at those reported are explained.				All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilities are identical and unmodified for all the products cited above.				
10	Signatur		Tanie	L A	anen/	Date			7/9/2015		
	Print Name / Title Daniel Havey IPv6 Program Manager										
See insti	uctions for fie	lds 1-12 on Page 4.			()	<u> </u>					
								-			

11 Suppliers Declaration of Conformity for USGv6 Products: Declared Capable Product Id: Windows Phone Stack			Stack I		and a second		Windows Phone 8						
	-		Context	Suppo	rted Capa	abilities I		USGv6 Testing Pr	rogram Results				
Spec /	Section	USGv6-v1 Profile Regularments	Configuration Option	Host	100		Test Suite Conformance/NPD	Test Lab / Result ID, Note #, or Component Ref	Test Suite Interoperability	Test Lab / Result ID, Note # Component Ref			
500-267	6.1	IPv6 Basic Requirements				-		Tal la l	Basic_V1.*_I	UNH IOL 18496			
		uipport of IPv6 base (IPv6 ICMPv6 PMTU ND)	.PvG-Base	P		-	Basic v1 ° C	HH QL 18494 UNH QL 18494	Basic VI. I	11H IQU 1849G			
		support of PMTU Discovery Protocol requirements	PMTU	P P	-	- 1	Basic_v1 * C SLAAC V1 * C	UNH IOL 10495	SLAAC VI.* I	UNH 101 18497			
	120	sipport of stateless address auto configuration	CLAAC			+ +	SLAAC V1 C	UNH IOL 18495	SLAAC VI	UNH IOL 18497			
	_	support of Creation of Global Addresses	Pr vAddr	Р	-	-	ell Test	134H OL 10493	Self Test				
		support of GLAAC privacy extensions	DHCP Clent	+	+	+	DHCP Client v1.* C		DHCP Client_vt.*_I				
-		support of stateful (OHCP) address auto- lipport of automated router prefix delegation	DHCP Pielix	+	+ -		Cell Test		Self Test				
	-	proport of meighbor discovery security extensions	GEND	+			gelf Test		Cell Test				
500-267	6.6	Addressing Requirements		1	-								
100-201	0.0	sugger of addressing architecture regis	Addr Arch	P			Addr Arch v1.° C	LNH- QL/18498	Addr Arch v1.* I	UNH IOL 18499			
	-	support of crypto prachically generated aridresses.	CGA	1			Cell Test		Celf Test				
500-267	6.7	IP Security Requirements											
	-	support of the IP security architecture	IF'secv3				Psecv3_v1.*_C		IPsecv3_v1.*_I				
		support for automated key management	'KEv2				IKEv2_v1.1_C		IKEv2_v2.* I				
	-	support for encapsulating security payloads in IP	ESP				ESPv3_v1,* C		ESP v1.º I				
500-267	6,11	Application Requirements	9										
		support of DNS clientiresciver functions	DNG-Client				Cell Test		elf Test				
		support of Gocket application program interfaces	SOCK	1			ell Test		ef Test	+			
		support of "Pv6 uniform resource identifiers	URI	1	1		Fell Test		eff Test	+			
		support of a DNS server application	DNG Server		-		Celf Test		DHCP Serv v1.* 1	+			
		support of a DHCP server application	DHCP Server	-	-		est Test		DHUP Serv VI. 1				
500-267	6.2	Routing Protocol Requirements		-		-			OSPFv3_v1.1				
		support of the intra-domain sinterior) routing	IGW	-			Cell Test		BGP v1.* I	t			
		support for inter domain (exterior) routing	€GiVV	+			Jell Test		BGF_VII				
500-267	6.4	Transition Mechanism Requirements		-	-	-	Cell Test		Self Test	1			
	-	support of interoperation with IPv4 only systems	IPv4	-		+	Cell Test		Self Test	†·			
		sileport of tunneting IPv6 over IPv4 MPLS services	6FE	+	-	-	60.1621	+	Self Test				
2500-267	6.0	Network Management Requirements	SNMP		-	+	ed Test		Celf Test				
500-267	6.9	support of network management services Mutticast Requirements	C1141C17	-	-	1	203 1031						
250U-267	6.9	support of basic multicast	Meast	1	1	1	elf Test						
	+	full support of multicast communications	OUM	-	+	†	ell Test		"elf Test				
500-257	6 10	Mobility Requirements	Co. Ale	1	1	-							
JULY ZTH	0.10	support of mobile IP capability	MIP				"e'f Tost		Left Test				
	+	support of mahile network capabilities	NEMO			1	eff Test		eff Test				
500-207	6.3	Quality of Service Requirements		1	1								
1770-201	0.0	support of Differentiated Services capabilities	D3				Cell Test		Cell Test				
2500×267	6.12	Network Protection Device Requirements											
		support of common NPD rects	NPD				N1 N2 N3 N4_v1.3			1			
	1	support of basic firewall daeabaties	FVV				N1 FW_v1.3			200.0			
	1	support of application firewall capabilities	APFW		1		Self Test						
	I	support of intrusion detection capabilities	:03	-		+	N3_IDS_v1 3			+			
-		support of intrusion protection capabilities	IP!	-	-		N4_IPS_v1.3						
P500-267	6.5			1	1	-	0.00	-	I alf Tank	-			
		support of robust packet compression services	ROHC	P	1-	1 -	Gelf Test	Celf Declaration	elf Test	ell Declaration			
	-	support of link technology [O 1]	Link=Ethemet	P	-	-	Celf Test	en Demaration	DEI 1631	T Decidio.ion			
	-				+	-	+						
	-	repeat as needed support of link technology	Link=	-	-				. A . A				
12		< Check HERE if this stack's DOC include	les additional	Inform	ation a	bout tes	sted capabilities and	options on an attached page	e 3 of notes.				
Level	Level	of support for USGv6-v1 Requirements for capabi			Color	Color Indication of USGv6-v1 Recommended Level of Support for device type I stack role,							
		SDOC makes no declaration, for this capability			200		Indicates capability that is recommendent as mandatory (unconstitional MUST) in the UCGv6-v1 Pro						
P		d required tests of USGv6-V1 requirements for these				Indicates catability that is unusal for a given device type i stack role. Do not select without careful analysis indicates catability that is left optional, ocnational by the recommediations of the USGv6-v1 Profile.							
N P			ts for this										
X 11		re notes gare for details on the level of suggent of UCGv6-v1 reequirements for this Gv6 capability not supported in product.					The state of the s						
A	1000V	a capability not supported in product.					Annual Control of the						

	S Decidiani	on of Conto	rmity <u>for</u> USGv6 Products: <u>Notes Pa</u>	ge and Detailed	Test Re	sults S	ummar			USGv6	-v1 SDOC-v1.10 Page
Field	Product (d:					Stack I	d;	2 /			
13				Context/	Supp	exted Capabilities			Notes about USG		
	Spec / Reference	Canton	100 4 40-41 5-41	Context / Configuration Option				Test Suite	_	v6-v1 Capabilities Test Suite	
Note #	Marhiatica	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Test Lab / Result ID, Note	Interoperability	Test Lab / Result ID. Note
	1.0			8		1 [
					-	-		h			<u> </u>
A- 10											
	1				i	i l					
		S 4-			1	il		L j		-	
				1	1						
		·				1					_250,650
	- 5										
					ī	TT		T		44	
				-		i					1
											-
		T			T						
-								L			1120
					T						
	-					i					
					T						
				1	_					Appeal of the second	
-		7			7	1					
]	!					
											-
	-	-									
200	20111										
-					1	4					
200							-				
		1			_	1					1
							_				

Suppliers Declaration of Conformity for USGv6 Description and Instructions

Field

Description and Instructions

The Document Requiring Conformity Identifies the profile version

mplemented. Not a user completable field

USGv6-v1 SDOC-v1.10 Page 4

Description and Instructions

Summary of Results. The format of this table mirrors the USGv6-v1 0 capabilities.

checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities.

are fisted as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Test Lab Result ID. The Discussion includes details about the test result that will be

General This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1.

Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at http://www.antd.nist.gov/usgv6/testing.html. Contact usgv6-project@antd.nist.gov

2	Product Identifier Supplier's concise name for the product declared		Product Id/Stack Id The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	Suppliers Name, Address and Contact Details Company name and point of contact for SDOC questions, street address, phone and email		Host, Router and Network Protection (NPD) columns identify 'preferred' options cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	Product as Tested/Declared Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc.)		Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1 0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	Product Family A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.
6	USGv6 Capability Summary The USGv6 stack implementation summary as identified by the + notation described in the USGv6 profile. Appendix A For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2)		Cells marked <i>Self Test</i> have no associated public test suite. If implemented by the supplier, the required adjacent annotation is " <i>Self Declaration</i> ". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	Self Contained or Composite SDOC If this SDOC relies on the test results of other disinct products, list the Supplier & Product (DIStack IDs referenced and attach those original SDOCs to this one	12	Additional Options Tested Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile Explanations on the page following the results summary Headings and Special Notations as described
8	Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC		Options for Test Lab and Result Id: Currently 3 cases (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability, (3) See attachment or note 'N', where the supplier explains variations in greater detail
9	Supplementary Attestations Suppliers disclosure of IPv6 only capabilities, multiple stacks present, product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply	13	Stack-1 Notes Instructions The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.
10	Signature Block Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.		Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements. Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with

disclosed to the buyer