Disported Capabilities Test Suite Component Ref Disported Esting Program	Scalabor USS-Side of Pratitile Requirements	Product Id:	McAfee Web Gateway Stack Id:			Stack Id:			7.5.0.1	
Section Procedure Proced	Delication Pog. Base Pog. Basic v1.* C Basic v1.* C SLAAC.V1.* C Slad Test Slad	Spec /	1	Configuration	Suppor	ted Capabilities	Test Suite	USGv6 Testing P Test Lab / Result ID, Note #, or	rogram Results Test Suite	Test Lab / Result ID. Note
Bulgorid of Pink Isses (Pink ICMPne) Pink Saave Pink Pink	MITU.ND IPv6-Base PMTU	6.1	IPv6 Basic Requirements	Option	_		Conformance/NPD	Component Ref	Interoperability	Component Ref
SULDORI of PAPITU Discovery Protocol regularements SLAAC - AM P	Internents		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	P		v1.* C	UNH-IOL/19888	Racio V4 * I	UDRON ICI HINI
SANC P	SLAAC-O(M)		support of PMTU Discovery Protocol requirements	PMTU	ס"		C	UNH-IOL/19888	Basic V1.*	INH-IOI/19890
Support of such makes of the control of such support of such support of such makes of the control of such support of such such support of such support of such such such support of such such such support of such such such such such such such support of such such such such such such such such	Self Test Self		support of stateless address auto-configuration	SLAAC	ס		ဂ	UNH-IOL/19889	SLAAC-V1.* I	UNH-IOL/19891
Building	REPAY Capabilities DRCP-Client Capability Capabil	1	Support of Class privacy extensions	SLAAC - c(M)	٥		C	UNH-IOL/19889	SLAAC-V1.* I	UNH-IOL/19891
Support of pulproprietal generations in SEND SE	Color Children C		support of stateful (DHCD) address auto	PIVAGGI			Self Test		Self Test	
Sea Addressing participations Service	Addr-Arch P Addr-Arch Arch		support of automated router prefix delegation	DHCP-Prefix			Client v1.		DHCP_Client_v1.*	
S. B. Addrassing Requirements Addr Arch P	ture regits Addir-Arch P Addr Arch V1.* C GA Self Test Addir-Arch P Self Test Different IKEV2 Basement IKEV		support of neighbor discovery security extensions	SEND		1	Self Test		Self Test	
Support of backgrown of addressing archinecture reads	Addr-Arch	6.6	Addressing Requirements						Och Leot	
Bupport of cyptopethically generated addresses CGA Seri Test Seri Test Support of the P security architecture Psecot	Self Test Self		support of addressing architecture reqts	Addr-Arch	ס		Addr Arch_v1.* C	UNH-IOL/19892	Addr Arch v1.*	UNH-IOL/19893
Beautify indigenerated by product of the Paccurity arichitecture. IREC2 IREC2 VI.* C IREC2 VI.*	IPsecv3 v1.* C IRSev3 v1.* C IRSev6 v1.* IRSev6 v1.* C IRSev6 v1.* IRSev6		support of cryptographically generated addresses	CGA			Self Test		Self Test	01111101110000
Belignost of the Prescript Authority Exposeds in Pieces Prescript Authority Exposeds in Pieces	Imagement Image	0./	emport of the ID country carbinet.							
Support for price in communications in Pices Support of Souri application in Country physicals in Pices Support of Souri application in Country physicals in Pices Support of Souri application in Country physicals in Pices Support of Pices application in Country physicals in Souri Real Support of Pices application in Country services in Souri Real Support of Pices application in Country services in Souri Real Support of Pices application in Country services in Souri Real Support of Inflational Inflation in Country i	Mads in IP		support of the in security and intecture	1			IPsecv3_v1.*_C		IPsecv3_v1.*_I	
Set 11 Application Requirements SOCK SOCK SOCK SOCK SUpport of Social application program interfaces SOCK SOCK Social Test Support of In No. Secretal application program interfaces SOCK Social Test	functions DNS-Client Self Test Solf Test Self Test polication DNS-Server DPIcation DNS-Server Services SOLK Self Test Services SNMP Self Test		Support for encapsulating security navigade in ID	1			17.17.2 V1.1 C		IKEv2_v2.*_I	
support of DNS client/resolves functions Spiral support of DNS client (Spiral Spiral S	functions DNS-Client Self Test Interfaces SOCK Self Test Centifiers URI Self Test Splication DNS-Server Self Test Splication DHCP-Server Self Test Services SNMP Self Test Services SNMP Self Test Sel	6	Application Requirements				ESPV3_V1.*_C		ESP_v1.*_I	
Support of Broken Engineering Sources Markets Saviers	Interlaces SOCK Self Test		Support of DNS client/resolver functions	122			0 5 1			
Support of IP-86 uniform isolation (IRI) Support of IP-86 uniform isolation (IRI) Support of IRI (IRI) Service application (IRI) Support of IRI (IRI) Company (IRI) Support of IRI (IRI) Company (IRI) (IRI) (IRI) Support of IRI (IRI) (IRI) (IRI) (IRI) (IRI) (IRI) (IRI) Support of IRI) (IRI) (IRI) (IRI) (IRI) (IRI) (IRI) (IRI) (IRI) Support of IRI) (IRI)	dentifiers DRIC-Server DRIC-S		support of Socket application program interfaces	- 1			Self Test		Self Test	
Support of a DNS server application DHCP-Server Self-Rest Support of the interdemental protocols Regularements Support of the interdement (action) rotting Support of interdement (action) systems Sept Test Sept Test Support of interdement (action) systems Sept Test Sept Test Sept Test Support of interdement (action) systems Sept Test Sept Test Support of interdement (action) systems Sept Test Sept Test Sept Test Support of interdement (action) systems Sept Test Sept Test Support of interdement (action) systems Sept Test Sept Test Support of interdement (action) systems Sept Test Sept Test Support of interdement (action) systems Sept Test Sept Test Support of interdement (action) support o	polication DNS-Server Self Test Self Test polication DHCP-Server Self Test services EGW Self Test services EGW Self Test services SNMP Self Test services SNMP Self Test services SNMP Self Test multicast incations SSM Self Test services SNMP Self Test services SNMP Self Test services SNMP Self Test services SNMP Self Test services NEMO Self Test services PW Self Test services PW Self Test services IDS Self Test		support of IPv6 uniform resource identifiers	1			Self Test		Self Test	
Secretary Support of the Intra-domain (interior) noutring protocols Self Test Self Test Support of the Intra-domain (selection) noutring protocols Self Test Sel	polication DHCP-Server Self Test c) routing IGW Self Test protocols EGW Self Test protocols EGW Self Test services SNMP Self Test services SNMP Self Test services SNMP Self Test pabilities Mcast NEMO Self Test pabilities NEMO Self Test pabilities DS Self Test pabilities NPD Self Test pabilities APFW Self Test pabilities ROHC Self Test pabilities ROHC Self Test pabilities ROHC Self Test pabilities APFW Self Test APFW AN AN APFW AN AN APFW AN APFW AN AN APFW AN APF		support of a DNS server application	DNS-Server			Self Test		Self Test	
Second Requirements	systems IPv4 Self Test systems IPv4 Self Test services 6PE Self Test services SNMP Self Test services SNMP Self Test services SNMP Self Test multicast Mcast SSM Self Test nications SSM Self Test pabilities NEMO Self Test pabilities NEMO Self Test pabilities NPD Self Test pabilities NPD Self Test pabilities NPD NINZIN3IN4 v1.3 pabilities FW Self Test pabilities FW Self Test pabilities FW Self Test pabilities APFW Self Test pabilities FW Self Test pabilities FW Self Test pabilities SIDS NINZIN3IN4 v1.3 pabilities FW Self Test pabilities FW INTITIONAL Self Test pabilities FW INTI		server application	DHCP-Server			Self Test		DHCP Serv v1 * 1	
Support of rine intra-domain (interior) routing (SeW) 6.4 Transition Mechanism Requirements Support of interioration (interior) systems (PVA Support of interioration with IPV4-only systems (SeW) Sew Test (Sew) Support of interioration with IPV4-only systems (SeW) Sew Test (Sew) Sew	systems IPv4 Self Test systems IPv4 Self Test services GPE Self Test services SNMP Self Test services SNMP Self Test multicast Mcast SSM Self Test nications SSM Self Test pabilities NEMO Self Test pabilities NEMO Self Test pabilities NPD Self Test pabilities NPD Self Test pabilities NPD NPW Self Test pabilities FW Self Test pabilities FW Self Test pabilities FW Self Test pabilities APFW Self Test pabilities FW Self Test pabilities Services APFW Self Test pabilities FW Indicates capability that is processory for these capability that is processory for this capability. Indicates capability that is	6.2								
6.4 Interview declaration for the process of the pr	services SNMP Self Test		support of the intra-domain (interior) routing	IGW			Self Test		OSPFv3 v1.* I	
Support of interceptation with IPA-dayle services appeared to interceptation appeared to interceptatio	services 6PE Self Test services SNMP Self Test multicast Mcast SSM Self Test apability. MIP pabilities NEMO Self Test spabilities NPD NIN2IN3IN4_v1.3 spabilities NPD Self Test spabilities NPD NIN2IN3IN4_v1.3 services NPD Self Test spabilities NPO Self Test spabilities NP	2	support for inter-domain (exterior) routing protocols	EGW			Self Test		BGP_v1.*_I	
support of tunneling IPv6 over IPv4 MPLS services 8.8 Network Management Requirements Support of mobile pervices support of mobile IP capability. 8.9 Multicast Requirements SUPPORT of multicast communications SSM SSM SSM SSM SSM SSM SSM SSM SSM SS	Services SNMP Self Test		support of interoperation with IPv4-only systems	IPvA			Colf Tool			
Auditicast Requirements SIMMP Self Test	Self Test Self Test		support of tunneling IPv6 over IPv4 MPLS services	6PE			Self Test		Self Test	
6.9 Multicast Requirements Sign Test Sign	multicast Mcast Self Test apability. MIP apabilities NEMO Babilities DS pabilities NPD PD reqts NPD PD reqts NPFW pabilities APFW pabilities IPS pabilities IPS pabilities IPS pabilities PS pabilities APFW pabilitie	6.8	Network Management Requirements						Self Test	
Self Test Self Test	multicast Mcast Self Test apability. MIP	20	Support of network management services	SNMF			Self Test		Self Test	
6.10 Mobility Requirements 8.3 Quality of Service Requirements 9.3 Support of Differentiated Services capabilities 1.4 Network Protection Device Requirements 1.5 Support of Differentiated Services capabilities 1.6 Support of Intrusion protection capabilities 1.7 Support of Intrusion protection capabilities 1.8 Support of Intrusion protection capabilities 1.8 Support of Intrusion protection capabilities 1.9 Support of Intrusion protection capabilities 1.0 Suppor	apabilities apabilities pabilities APFW pabilities AN IPS v1.3 AN IPS v1	0.0	support of basic multicast	Moset			Oale Tank			
Self Test Support of mobile in Example Self Test	pabilities NEMO Self Test pabilities DS Self Test pabilities DS Self Test pabilities PD NEMO NEMO Self Test pabilities PD NAINZINJIN4 v1.3 pabilities APFW Self Test pabil	5.	full support of multicast communications	SSM			Self Test		Colf Tost	
support of inferentiated Services capabilities 6.12 Network Protection Device Requirements support of Differentiated Services capabilities Support of Device Requirements Support of Device Common NPD reduces Support of Device Requirements Support of Device	apabilities pabilities pabilities pabilities pabilities pabilities pabilities PD reqts APFW A	6.10	Mobility Requirements						OBIT TOOL	
6.3 Quality of Service Requirements Support of Differentiated Services capabilities IDS Support Of Differentiated Services Self Test Self Declaration Indicates capability Indicates capability that is recommended Level of Self Declaration of USGv6-v1 Recommended Level of Self Declaration	pabilities DS Self Test ts NPD Self Test pabilities FW Self Test pabilities APFW Self Test pabilities IDS N1DS N1 FW v1.3 pabilities IPS NPD N4 IPS v1.3 pabilities PS NPD N4 IPS v1.3 pabilities APFW Self Test pabilities PS NA IPS v1.3 pabilities PS Self Test ggy [C:1] Link= Ethernet P Self Test ggy [C:1] Link= Ethernet P Self Test ggy [C:1] Link= Capability. Color Indicates capability that is or these capabilities. Indicates capability that is USGv6-v1 reequirements for this capability. Indicates capability that is USGv6-v1 reequirements for this capability. Indicates capability that is		support of mobile IP capability.	MIP			Self Test		Self Test	
Support of Differentiated Services capabilities 6.12 Network Protection Device Requirements Support of Intrusion Nature Support of Intrusion Support of Intrusion Support of Intrusion	pabilities PD reqts PW PW PW PW PW PW PW PW PW P	6 13	Ouality of Service Requirements	NEMO			Self Test		Self Test	
Beink - SDOC makes no declaration for this capability.	pabilities FW Self Test pabilities APFW Self Test pabilities IPS NA IPS V1.3 pabilities APFW Self Test pabilities IPS NA IPS V1.3 pabilities IPS NA IPS V1.3 pabilities IPS Self Test pabilities ROHC Self Te		support of Differentiated Services capabilities	DS			Self Test			
support of common NPD reqts Support of papiciation flewall capabilities Support of application flewall capabilities Support of intrusion detection capabilities Support of intrusion detection capabilities Support of intrusion protection capabilities IDS Support of intrusion detection capabilities IDS Support of intrusion protection capabilities IDS Support of intrusion detection capabilities IDS N4 IPS v1.3 Self Test Self Declaration Self Declaration Color Indicates and options on an attached page 3 of n Indicates capability that is recommended Level of Stack role. Indicates capability that is left optional / conditional by the recommended in product.	pabilities FW NPD NINZINJIN4 v1.3 pabilities FW Self Test Self Test pabilities IPS NA IPS v1.3 pabilit	6.12	Network Protection Device Requirements				Opti Last		Self lest	
support of basic frewall capabilities support of application firewall capabilities support of application frewall capabilities support of intrusion detection capabilities support of intrusion protection capabilities ROHC support of robust packet compression services support of intrusion detection capabilities ROHC Self Test Self Declaration Self Test Self Declaration Self Test Self Declaration Self Test Self Declaration Self Declaration Self Test Self Declaration Indicates capabilities and options on an attached page 3 of notes page for details on the level of Support of USGv6-v1 reequirements for this capability. Indicates capability that is left optional / ocnditional by the recommended Indicates capability that is left optional / ocnditional by the recommended	pabilities			NPD			N1 N2 N3 N4 v1.3			
support of application firewall capabilities support of intrusion detection capabilities support of intrusion protection capabilities support of intrusion detection capabilities support of recting support of intrusion capabilities support of recting support of intrusion capabilities support of intrusion capab	pabilities APFW Self Test pabilities IDS N3 IDS_v1.3 pabilities IPS N4 IPS_v1.3 pabilities IPS N4 IPS_v1.3 pabilities ROHC Self Test Discription Self Test Discription		support of basic firewall capabilities	FW			N1_FW_v1.3			
support of intuition protection capabilities in S. Link Specific Technologies support of includes additional information about tested capabilities and options on an attached page 3 of notes page for details on the level of support of USGv6-v1 reequirements for this capability. Level of sage for details on the level of support of USGv6-v1 reequirements for this capability. Support of invition protection capability. ROHC Self Test Self Declaration Self Test S	pabilities IPS N4 IPS v1.3 pabilities ROHC Self Test Se		SUPPOR Of application firewall capabilities	APFW			Self Test			
Self Test Self Declaration	services ROHC Self Test ggy [O:1] Link= Ethernet P Self Test ggy [O:1] Link= Ethernet P Self Test chnology Link= chnology Link		support of intrusion protection capabilities	PS			NA IDS V1.3			
support of robust packet compression services ROHC Self Test Self Declaration Self Test Self Declaration	services ROHC Self Test 293 [O:1] Link= Ethernet P Self Test 203 [O:1] Link= Self Test 204 Self Test 205 Includes additional information about tested capabilities and of self test 206 Indicates capability that is capability. Indicates capability that is capabi	6.5	Link Specific Technologies	= 0			0.1 A C 11 4A1			
Check HERE if this stack's DOC includes additional information about tested capabilities and options on an attached page 3 of notes page for details on the level of support of USGv6-v1 reequirements for these capability. See notes page for details on the level of support of USGv6-v1 reequirements for this capability. Indicates capability that is left optional / ocnditional by the recommendation	ogy [0:1] Link= Ethernet P Self Test chnology Link= chnology Link		support of robust packet compression services	ROHC			Self Test		Splf Toet	
Check HERE if this stack's DOC includes additional information about tested capabilities and options on an attached page 3 of no	includes additional information about tested capabilities and or capability. Color Indication Indication Indicates capability that is concluded capability. Indicates capability that is Ind		support of link technology [0:1] L	ink= Ethernet	О			Self Declaration	Self Test	Self Declaration
Level of support for USGv6-v1 Requirements for capability. Blank - SDOC makes no declaration for this capability. Passed required tests of USGv6-v1 requirements for these capabilities. See notes page for details on the level of support of USGv6-v1 reequirements for this capability. See notes page for details on the level of support of USGv6-v1 reequirements for this capability. Indicates capability that is unusal for a given device type / stack role. See notes page for details on the level of support of USGv6-v1 reequirements for this capability. Indicates capability that is left optional / ocnditional by the recommeded uncommeded.	includes additional information about tested capabilities and of capability. Color Indication Indication Indicates capability that is or these capabilities. I USGv6-v1 reequirements for this capability. I Indicates capability that is Indicates capability that is Indicates capability that is Indicates capability.		(repeat as needed) support of link technology []	ink:						
Level of support for USGv6-v1 Requirements for capability. Blank - SDOC makes no declaration for this capability. Passed required tests of USGv6-v1 requirements for these capabilities. See notes page for details on the level of support of USGv6-v1 reequirements for this capability. See notes page for details on the level of support of USGv6-v1 reequirements for this capability. Indicates capability that is unusal for a given device type / stack role. Indicates capability that is left optional / ocnditional by the recommeded in product.	r capability. Color Indication Indication Indicates capability that is fuscion-v1 reequirements for this capability. (USGv6-v1 reequirements for this capability. Indicates capability that is fuscional indicates		< Check HERE if this stack's DOC include	s additional in	formati	on about fact				
Level of support for USGv6-v1 Requirements for capability. Color Indication of USGv6-v1 Recommended Level of Stable	r capability. Color Indication Indication Indication Indication Indicates capability that is or these capabilities. I USGv6-v1 reequirements for this capability. Indicates capability that is Indicates capability that is Indicates capability that is Indicates capability.			e additional in	TOTHIGH	on about lesi		puons on an attached page 3	of notes.	
Blank - SDOC makes no declaration for this capability. Passed required tests of USGv6-V1 requirements for these capabilities. See notes page for details on the level of support of USGv6-v1 reequirements for this capability. USGv6 capability not supported in product. Indicates capability that is unusal for a given device type / stack role. Indicates capability that is left optional / ocnditional by the recommedation.	ility. Indicates capabilities. Indicates cabability that is f USGv6-v1 reequirements for this capability. Indicates capability that is f USGv6-v1 reequirements for this capability. Indicates capability that is f use for the capability that is fully some anticonstant of the capability that is fully some anticonstant of the capability that is fully some anticonstant of the capability.		support for USGv6-v1 Requirements for capabilit	.		Color	indication	of liggys at Docommonded Law		
Passed required tests of USGv6-V1 requirements for these capabilities. See notes page for details on the level of support of USGv6-v1 reequirements for this capability. USGv6 capability not supported in product.	or these capabilities. Indicates capability that is fusions and indicates capability that is fusion to the capability that is fusio		DOC makes no declaration for this capability.		de contractor de	_		O Cagre-y Recommended Leve	or support for device	type / stack role.
See notes page for details on the level of support of USGv6-v1 reequirements for this capability. USGv6 capability not supported in product. Indicates capability that is left optional / ocnditional by the recommedation of the commedition of the commedition of the capability not supported in product.	/ USGv6-v1 reequirements for this capability. Indicates capability that is //www.antd.nist.gov/usgv6/test-specifications.html		equired tests of USGv6-V1 requirements for these ca	pabilities				recommendend as mandatory (unco	nditional MUST) in the U	SGv6-v1 Profile.
USGv6 capability not supported in product.	/www.antd.nist.gov/usgv6/test-specifications.html		s page for details on the level of support of USGv6-v	reequirements fo	r this can			uriusal for a given device type / stack	role. Do not select with	out careful analysis.
	/www.antd.nist.gov/usgv6/test-specifications.html		apability not supported in product.	- codanonione io	i illo cal			len optional / ochditional by the recor	nmedations of the USGv	3-v1 Profile.
	/www.antd.nist.gov/usgv6/test-specifications.html									
/www.antd.nist.gov/usgv6/test-specifications.html	and the second s	CONTRACTOR STANDARD CONTRACTOR CO								

Spec / Section USGv6-v1 Profile Requirements Configuration Host Option Host Institute of the Profile Requirements Configuration Host Option Host Institute of the Profile Requirements Configuration Host Institute	Field Product Id:	Field Product Id: McAfee Web Gateway, software v7.5.0.1 Stack Id:	re v7.5.0.1	10	Stack Id:	·		Mont	cal stack on all mo	on all models
THE CONTRIBUTION OF THE PARTY O	Spec / Reference	IIRQuayd Drofile Descriptions of	Context / Configuration	Support	ted Capal		Test Suite	Notes about USGv	6-v1 Capabilities. Test Suite	
Discussion: Discu		e riguspus ty pe santon ar pe denoral consider			100		Company Services	rest Lab / Nesun ID, Note	пнегорегающу	lest Lab / Kesun ID
Discussion: Discu	iscussion:	STORY OF STREET OF THE PROPERTY OF THE PROPERT						Paris Bakkinan ar		
Discussion: Discussion: Discussion: Discussion: Discussion: Discussion: The property of	2	ACCOUNTS BOOK STANDARD WITH TO DO NOT THE CONTROL OF THE CONTROL O		- F						
Discussion:	iscussion:		1877 P							
Discussion: Discussion:	ن ا						AO strucete il ansi nettro sette i all'e	White the second		
December: Committee Commi	iscussion:	SAS (character) and property of compact of the comp	Object	10 NO 80		80 38	8 7 10 10 10 10 10 10 10 10 10 10 10 10 10	Divide Market and Tables		
Discussion: Discussion:	4									
Discussion: Discu	iscussion:	n enektr out out 2 in julian 9 separat est julian 19 separat est j				thought.				
Discussion: Discussion about this Product / Stuck's capabilities:	Ch	184 18 2000 1842 27 CH SHE 65 185 185 185 185	4.5 8.438				e despective despe			
Discussion: Discussion about this Product / Stack's capabilities:	iscussion:	and the state of t								
Discussion: Discu	o	with the Proof was left weekpring the e	0		Å		18 - 19 - 19 - 19 - 18 - 18 - 18 - 18 -	to test sector, setting		
Discussion: Discussion: Discussion: Discussion: Discussion: Discussion: Discussion: Discussion: Discussion: Discussion about this Product / Stack's capabilities:	scussion:			10.00				CSD MAD III D		
Discussion: Discussion: Discussion: Discussion: Discussion: Discussion: Vendor's General Notes / Discussion about this Product / Stack's capabilities:	7							The state of the s		
Discussion: Discussion: Discussion: Discussion: Discussion: Discussion: Discussion: Discussion about this Product / Stack's capabilities:	scussion:							TO THE WILLIAM TOP		
Discussion: Discussion: Discussion: Discussion: Vendor's General Notes / Discussion about this Product / Stack's capabilities:	00			2	5	Š				
Discussion: Discussion	scussion:									
Discussion: 10	9	erety is obtained by the second contraction of the second	2	28	U43818100 19		obaspeo o mae			
Discussion: Vendor's General Notes / Discussion about this Product / Stack's capabilities:	scussion:					3 8 5 7 8 4		A CONTRACTOR OF THE STATE OF TH		destinating time is place, and mid-injury proposed in the injury propagate.
Discussion: Vendor's General Notes / Discussion about this Product / Stack's capabilities:	10	The sample of the second particle of the same second three same second to the same second three second to the same second to th	1000	100 J	2	8				
Vendor's General Notes / Discussion about this Product / Stack's capabilities:	scussion:						Med Trongentier	1000 C 2000 C 2000 C		
The control of the co	endor's General Notes / Discussion a	bout this Product / Stack's capabilities:								
THE THE PROPERTY OF THE PROPER										
THE PROPERTY OF THE PROPERTY O										

 Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov. General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page

-	all bolon in	Hallbord Held Strott bolom, trotto occasio receite an indicatina de manageri accasio receite de accasio de describenta de manageri de de la companya de la c	0,000	girmin common action of contracting contra
	Field	Description and Instructions	Field	Description and Instructions
	>	The Document Requiring Conformity: Identifies the profile version	<u>-</u>	Summary of Results: The format of this table mirrors the USGv6-v1.0
		implemented. Not a user completable field.		capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of t
				and the same that an another disease with another than the same and the same

- 2 Product Identifier: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- 6 USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.

ဖ

3 Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the "Musts" in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.

13 Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.

Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.