Suppli	ers Declaration of Co	onformity for USGv6 I	Products				USGv6-v1 SDOC-v1.10 Page 1			
1	The Document Requ	uiring Conformity:					USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)			
2						ndows 8 and Windows Server 2012				
3		ddress and SDOC Co	ntact Deta	ils						
Micros	oft Corporation									
4	Product as Tested/E	Declared: Product Ider	tested.							
				Windows 8 and Wind						
5	Product Family (other						ı). Check Product Family attestation below.			
		A	iny hardwai	re capable of running Wi	ndows 8 or	Windows S	erver 2012			
6		. 1		•		•	SGv6 capabilities below and include a detailed test result			
	įsummary). <i>e.g. exam</i>			<u>lost: IPv6-Base+Addr-Ard IPv6-Base+Addr-Arch+</u>						
7	Self Contained or Composite SDOC? (Must indicate one).									
YES	are addressed by orginal test results reported in this their own unique USGv6 S			their own unique USGv6 SD	pabilities of this product are provided by the use and/or integration of umodified components that have iOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's apabilities are provided by specific referenced components (product-id/stack-id).					
8	Additional Declarati	ons / Attachments: (L	ist supplier	r & product-id/stack-id for	r reference	d and attach	ned test results in the case of composite products).			
	Component Supplie	r	Product (D:	Stack ID:		Notes:			
[1]										
[2]										
[3]										
[4]			T							
9	Supplementary Atte	stations (Answer all).								
	1	capabilities are invalidated ifthis product is operated in a dual stack (6 and 4)network					This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support Ipv4.			
	product. If no		pabilities test report for each unique IPv6 stack in the /ports not covered are documented, and how their Ipv6 is reported are explained.			All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilities are identical and unmodified for all the products cited above.				
10	Signature Print Name / Title	Daniel Havey IPv6 Pro	ogram Man	W/V	Date		7/9/2015			
	<u></u>	<u> </u>	ogram wan	991						
See instru	uctions for fields 1-12 on Page	ge 4.		J						

	Suppii	ers Declaration of Conformity for USGv6		lared C			i Test Results Summ	1	·	Sv6-v1 SDOC-v1.10 Page		
Product ld:		Windows 8 and Windows Serv	er 2012		Stack i	ld:		Windows 8	and Windows Serve	r 2012		
			Context /	Suppo	rted Capa	abilities		USGv6 Testing F				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID. Note #, or		
Reference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref		
SP500-267		IPv6 Basic Requirements										
		support of IPv6 base (IPv6 ICMPv6 PMTU ND)	IPv6-Base	Р			Basic_v1.*_C	UNH-IOL/12222	Basic_V1.*_I	UNH-IOL/12226		
		support of PMTU Discovery Protocol requirements	PMTU	Р			Basic_v1.*_C	UNH-IOL/12222	Basic_V1.*_I	UNH-IOL/12226		
		support of stateless address auto-configuration	SLAAC	P		<u> </u>	SLAAC-V1.*_C	UNH-IOL/12223	SLAAC-V1.*_I	UNH-IOL/12227 UNH-IOL/12227		
		support of Creation of Global Addresses	SLAAC - c(M)	P			SLAAC-V1.*_C	UNH-IOL/12223	SLAAC-V1.*_I Self Test	UNH-101/12/2/		
		support of SLAAC privacy extensions	PrivAddr	<u> </u>		<u> </u>	Self Test		DHCP_Client_v1.*_I	UNH-IQL/13997		
		support of stateful (DHCP) address auto-	DHCP-Client	Р			DHCP_Client_v1.*_C		Sell Test	ONH-10E 13991		
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test			
		support of neighbor discovery security extensions	SEND	-	<u> </u>	 	Self Test		36/1 7031	 		
SP500-267	6.6	Addressing Requirements	A data A sale	P	_		Addr Arch v1.° C	UNH-IOL/12224	Addr Arch_v1.*_I	UNH-IOL/12228		
		support of addressing architecture regts	Addr-Arch	P -	<u> </u>		Self Test	ONH-10D 12224	Sell Test	0.11110012220		
	<u> </u>	support of cryptograph:cally generated addresses	CGA				Sen rest		36,1103			
SP500-267	6.7	IP Security Requirements	IDa a su 3	-		-	IPsecv3 v1.* C		IPsecv3 v1.* I			
		support of the IP security architecture	IPsecv3 IKEv2	-	-	 	IKEv2 v1.* C		IKEv2_v2.*_I			
		support for automated key management	ESP	-		 	ESPv3 v1.* C	-	ESP v1.* I			
CD500 00**		support for encapsulating security payloads in IP	Ę SF			 	ESFV3_VIC			· · · · · · · · · · · · · · · · · · ·		
SP500-267	6.11	Application Requirements support of DNS chent/resolver functions	DNS-Client	 		 	Self Test	 	Self Test	 		
			SOCK	-	-	_	Sell Test		Self Test	· · · · · · · · · · · · · · · · · · ·		
		support of Socket appl:cation program interfaces support of IPv6 uniform resource identifiers	URI			\vdash	Self Test		Self Test			
		support of a DNS server application	DNS-Server	 			Self Test		Self Test			
		support of a DHCP server application	DHCP-Server	 		 	Self Test		DHCP_Serv_v1.*_I			
SP500-267	6.2	Routing Protocol Requirements	Bilor -ociver	_		 -	001031					
3F300-207	0.2	support of the intra-domain (interior) routing	IGW				Self Test	·	OSPFv3_v1.*_I	<u> </u>		
$\overline{}$		support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP_v1.*_I			
SP500-267	6.4	Transition Mechanism Requirements		 		i						
0. 500 20.	0.4	support of interoperation with IPv4-only systems	IPv4			i	Self Test	***	Self Test			
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test			
SP500-267	6.8	Network Management Requirements							Self Test			
		support of network management services	SNMP				Self Test		Self Test			
SP500-267	6.9	Multicast Requirements						·				
		support of basic multicast	Mcast				Self Test			<u> </u>		
		full support of multicast communications	SSM				Self Test		Self Test			
SP500-267	6.10	Mobility Requirements				Ľ.,						
		support of mobile IP capability	MIP				Self Test		Self Test			
		support of mobile network capabilities	NEMO		<u> </u>		Self Test	<u> </u>	Self Test			
SP500-267	6.3	Quality of Service Requirements										
		support of Differentiated Services capabilities	DS				Self Test		Self Test	ļ		
SP500-267	6.12	Network Protection Device Requirements										
		support of common NPD reqts	NPD				N1 N2 N3 N4_v1.3					
		support of basic firewall capabilities	FW			<u> </u>	N1_FW_v1.3					
		support of application firewall capabilities	APFW				Self Test	ļ				
		support of intrusion detection capabilities	IDS		ļ	-	N3_IDS_v1.3			 		
		support of intrusion protection capabilities	IPS			 	N4_IPS_v1.3			<u> </u>		
SP500-267	6.5	Link Specific Technologies							S-15.7			
		support of robust packet compression services	ROHC	<u> </u>	-		Self Test	Sall Declaration	Self Test	Self Declaration		
		support of link technology [O 1]	Link=Ethernet	Р.			Self Test	Self Declaration	Self Test	Gen Decidration		
			Links			-				-		
		(repeat as needed) support of link technology		ļ	<u> </u>	1	L		.1			
12		< Check HERE if this stack's DOC includ	es additional i	nforma	tion abo	out test	ed capabilities and o	ptions on an attached page	3 of notes.			
	la de	to the tigger of Danish and the conclusion	4			Color	Indication	on of USGv6.v1 Recommended Le	uel of Support for device	e type / stack role		
		assed required tests of USGv6-V1 requirements for these capabilities					Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis					
	See notes page for details on the level of support of USGv6-v1 reequirements for this capability						Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile					
N												
N		capability not supported in product.						<u></u>				
N		capability not supported in product.										
N X Test Suite -	USGv6	capab:lity not supported in product. USGv6 Test suite used for test. See http://www.anto-Abbreviation of accredited laboratory and its local id	I nist gov/usgv6/te	est-specif	calions.h	iml		Note # - reference to a - Supplier / Product / Stack ID of dis	detailed note about this c	apability or result on attached pag		

	s Declarati	on of Con	formity for USGv6 Products: Notes Pa	ige and Detailed	Test Ro			/		USGv6	-v1 SDOC-v1.10 Page 3
Field Product to		:			Stack (ld:	-				
13				Context /	Supp	orted Cap	obilities	Notes about US		v6-v1 Capabilities	
,,_, ,	Spec / Reference	Section	100 6 4 0-17 0 - 1	Configuration				Test Suite		v6-v1 Capabilities. Test Suite	1
Note #	Meterence	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Test Lab / Result ID. Note	Interoperability	Test Lab / Result ID. Note
		<u>.</u>									İ
			• • • • • • • • • • • • • • • • • • • •		-	±	<u>.</u>	<u> </u>			L
								200			
				•			İ				
				_+=		-	1	1			
					T		F				
								L		1222	1992
				T			-				
						ł				 	1
		į									·
					7			T			·
		'				!					
								<u>'</u>			L
					į						
						<u> </u>	L				<u> </u>
					I -						
						L	·	İ			
											i
									·		
								<u> </u>			
						!					
						4					
					·						
				İ							
		 			İ	L	L				
			•								

Field

Description and Instructions

The Document Requiring Conformity Identifies the profile version

mplemented. Not a user completable field

Description and Instructions

11 Summary of Results The format of this table mirrors the USGv6-v1 0 capabilities

options related to conditional implementation of selected capabilities

checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities.

are listed as subheadings with subsidiary functions as line items. Configuration

as the manufact, and This I down the action from a fathing many implication against facilities and a fathing many implication against the Department of the Company of the

General This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1.

Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at http://www.antd.nist.gov/usgv6/testing.html. Contact. usgv6-project@antd.nist.gov.

Field

2	Product Identifier Supplier's concise name for the product declared		Product Id/Stack Id The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	Suppliers Name, Address and Contact Details Company name and point of contact for SDOC questions street address phone and email		Host, Router and Network Protection (NPD) columns identify 'preferred' options cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	Product as Tested/Declared Product Identifier and detailed version information if this SDOC reports oringal test results (page 2). Include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc)		Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	Product Family A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.
6	USGv6 Capability Summary The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile Appendix A For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2)		Cells marked Self Test have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	Self Contained or Composite SDOC If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one	12	Additional Options Tested Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile Explanations on the page following the results summary Headings and Special Notations as described
8	Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC		Options for Test Lab and Result Id: Currently 3 cases (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory. (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability. (3) See attachment or note 'N', where the supplier explains variations in greater detail
9	Supplementary Attestations Suppliers disclosure of IPv6 only capabilities multiple stacks present, product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply	13	Stack-1 Notes Instructions The supplier may choose to use the Notes (page 3) in order to carify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.
10	Signature Block Wet link signature of the responsible product manager dated. Printed name and position title on the line below		Complete the Note by including the SpeciReference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements. Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.
	Further Description: http://www.antd.nist.gov/usgv6/testing.html, and NIS	ST SP	500-267 USGv6 Testing Program Users Guide available at the website.