Suppliers Declaration of Conformity for USGv6 Products		USGv6-v1 SDOC-v1.10 Page 1	
1	The Document Requiring Conformity:	USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)	
2	Product Identifier:	**vSRX**	
3	Supplier's Name, Address and SDOC Contact Details		
	Juniper Networks, 1194 North Mathilda Avenue, Sunnyvale, CA 94089-1206, SDOC contact- Bill Shelton- bshelton@juniper.net, 571-203-1825		
4	**Product as Tested/Declared:** *Product Identifier, version/revision information, details of configuration tested.*		
	15.1X49		
5	**Product Family** (other products using same IPv6 stack(s) to which these results are declared to apply). ***Check Product Family attestation below.***		
	vSRX, SRX1500, SRX4100, SRX4200		
6	**USGv6 Capability summary.** (For each distinct IPv6 stack in the product provide a summary of its USGv6 capabilities below and include a detailed test result summary). *e.g. example-prod-id/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arch+IPsec-v3+IKEv2+SLAC+Link=Ethernet.*		
	USGv6-v1-Router/NPD: FW+ IGW+EGW+ Link = Ethernet		
7	**Self Contained or Composite SDOC?** (Must indicate one).		
Yes	*All of the declared USGv6 capabilities of this product are addressed by orginal test results reported in this SDOC.*		*Some or all of the USGv6 capabilities of this product are provided by the use and/or integration of umodified components that have their own unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate which capabilities are provided by specific referenced components (product-id/stack-id).*

8	**Additional Declarations / Attachments:** *(List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).*			
	Component Supplier	Product ID:	Stack ID:	Notes:
[1]				
[2]				
[3]				
[4]				

9	**Supplementary Attestations** *(Answer all).*			
	Yes	*This product is fully functional in dual stack environments.That is, no claimed capabilities are invalidated ifthis product is operated in a dual stack (6 and 4)network environment.*	Yes	*This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support Ipv4.*
	Yes	*This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If not, the stacks/ports not covered are documented, and how their Ipv6 capabilities differ from those reported are explained.*	Yes	*All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilitiesare identical and unmodified for all the products cited above.*

10	Signature		Date	
	Print Name / Title	Bill Shelton, Federal Certifications and Policy		

See instructions for fields 1-12 on Page 4.

Product Id: vSRX   **Stack Id:** 15.1X49

Color key used below: (G) = green, (g) = gray.

Spec / Reference	Section	USGv6-v1 Profile Requirements	Context / Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note #, or Component Ref	Test Suite Interoperability	Test Lab / Result ID, Note #, or Component Ref
SP500-267	6.1	**IPv6 Basic Requirements**								
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	(G)	(G)		**Basic_v1.*_C**		**Basic_V1.*_I**	
		support of PMTU Discovery Protocol requirements	PMTU				**Basic_v1.*_C**		**Basic_V1.*_I**	
		support of stateless address auto-configuration	SLAAC				**SLAAC-V1.*_C**		**SLAAC-V1.*_I**	
		support of Creation of Global Addresses	SLAAC - c(M)				**SLAAC-V1.*_C**		**SLAAC-V1.*_I**	
		support of SLAAC privacy extensions.	PrivAddr				*Self Test*		*Self Test*	
		support of stateful (DHCP) address auto-configuration	DHCP-Client				**DHCP_Client_v1.*_C**		**DHCP_Client_v1.*_I**	
		support of automated router prefix delegation	DHCP-Prefix				*Self Test*		*Self Test*	
		support of neighbor discovery security extensions	SEND				*Self Test*		*Self Test*	
SP500-267	6.6	**Addressing Requirements**								
		support of addressing architecture reqts	Addr-Arch	(G)	(G)		**Addr_Arch_v1.*_C**		**Addr_Arch_v1.*_I**	
		support of cryptographically generated addresses	CGA				*Self Test*		*Self Test*	
SP500-267	6.7	**IP Security Requirements**								
		support of the IP security architecture	IPsecv3	(G)	(G)		**IPsecv3_v1.*_C**		**IPsecv3_v1.*_I**	
		support for automated key management	IKEv2	(G)	(G)		**IKEv2_v1.*_C**		**IKEv2_v2.*_I**	
		support for encapsulating security payloads in IP	ESP	(G)	(G)		**ESPv3_v1.*_C**		**ESP_v1.*_I**	
SP500-267	6.11	**Application Requirements**								
		support of DNS client/resolver functions	DNS-Client				*Self Test*		*Self Test*	
		support of Socket application program interfaces	SOCK		(g)		*Self Test*		*Self Test*	
		support of IPv6 uniform resource identifiers	URI				*Self Test*		*Self Test*	
		support of a DNS server application	DNS-Server				*Self Test*		*Self Test*	
		support of a DHCP server application	DHCP-Server				*Self Test*		**DHCP_Serv_v1.*_I**	
SP500-267	6.2	**Routing Protocol Requirements**								
		support of the intra-domain (interior) routing protocols	IGW	(g)	P		*Self Test*		**OSPFv3_v1.*_I**	UNH-IOL/23105
		support for inter-domain (exterior) routing protocols	EGW	(g)	P		*Self Test*		**BGP_v1.*_I**	UNH-IOL/23106
SP500-267	6.4	**Transition Mechanism Requirements**								
		support of interoperation with IPv4-only systems	IPv4			P	*Self Test*	Self Declaration	*Self Test*	Self Declaration
		support of tunneling IPv6 over IPv4 MPLS services	6PE				*Self Test*		*Self Test*	
SP500-267	6.8	**Network Management Requirements**							Self Test	
		support of network management services	SNMP	(g)	(G)	P	*Self Test*	Self Declaration	Self Test	Self Declaration
SP500-267	6.9	**Multicast Requirements**								
		support of basic multicast	Mcast	(G)	(G)		*Self Test*			
		full support of multicast communications	SSM				*Self Test*		*Self Test*	
SP500-267	6.10	**Mobility Requirements**								
		support of mobile IP capability.	MIP				*Self Test*		*Self Test*	
		support of mobile network capabilities	NEMO	(g)			*Self Test*		*Self Test*	
SP500-267	6.3	**Quality of Service Requirements**								
		support of Differentiated Services capabilities	DS		(G)	P	*Self Test*	Self Declaration	*Self Test*	Self Declaration
SP500-267	6.12	**Network Protection Device Requirements**								
		support of common NPD reqts	NPD			(G) P	**N1|N2|N3|N4_v1.3**	UNH-IOL/23104		
		support of basic firewall capabilities	FW	(g)		P	**N1_FW_v1.3**	UNH-IOL/23104		
		support of application firewall capabilities	APFW	(g)		P	*Self Test*	Self Declaration		Self Declaration
		support of intrusion detection capabilities	IDS	(g)			**N3_IDS_v1.3**			
		support of intrusion protection capabilities	IPS	(g)			**N4_IPS_v1.3**			
SP500-267	6.5	**Link Specific Technologies**								
		support of robust packet compression services	ROHC				Self Test		Self Test	
		support of link technology [O:1]	Link= Ethernet	(G)	(G) P	P	Self Test	*Self Declaration*	Self Test	*Self Declaration*
		(repeat as needed) support of link technology	Link=							

12	[yellow box]	< Check HERE if this stack's DOC includes additional information about tested capabilities and options on an attached page 3 of notes.

Level	Level of support for USGv6-v1 Requirements for capability.	Color	Indication of USGv6-v1 Recommended Level of Support for device type / stack role.
	Blank - SDOC makes no declaration for this capability.	(green)	Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.
P	Passed required tests of USGv6-V1 requirements for these capabilities.	(gray)	Indicates cability that is unusal for a given device type / stack role. Do not select without careful analysis.
N	See notes page for details on the level of support of USGv6-v1 reequirements for this capability.		Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.
X	USGv6 capability not supported in product.		

Test Suite - Specific USGv6 Test suite used for test. See: http://www.antd.nist.gov/usgv6/test-specifications.html   **Note #** - reference to a detailed note about this capability or result on attached page.

Test Lab / Result ID - Abbreviation of accredited laboratory and its local identifier for this test result.   **Component Ref** - Supplier / Product / Stack ID of distinctly tested component that provides this capability.

Field 13	Product Id:		vSRX		Stack Id:			Junos 15.1X49			
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Context / Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note
1											
Discussion:											
2											
Discussion:											
3											
Discussion:											
4											
Discussion:											
5											
Discussion:											
6											
Discussion:											
7											
Discussion:											
8											
Discussion:											
9											
Discussion:											
10											
Discussion:											

Notes about USGv6-v1 Capabilities.

Supported Capabilities

Vendor's General Notes / Discussion about this Product / Stack's capabilities: