Supp	uppliers Declaration of Conformity for USGv6 Products					USGv6-v1 SDOC-v1.10 Page 1						
1	The Document Requiring Conformity:					USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)						
2	Product	dentifier:				SonicO	A STATE OF THE PARTY OF THE PAR					
3	Supplier	s Name, A	Address and SDOC Co	ontact Details	1000							
Sonic	wall, Inc. 54	55 Great A	America Pkwy, Santa C	lara, CA - 95054 Usha Sanagala	a, Senior Pro	gram Manage	er, usanagala@sonicwall.com, 408-962-6248					
				-		,	,					
cwal	I, Product	as Tested	Declared: Product Ide	entifier, version/revision information	n, details of	configuration	tested.					
					3.5							
			processor and a second second									
5	Product	ramily (ot	her products using san	ne IPv6 stack(s) to which these re			). Check Product Family attestation below.					
				TZ Series, SOHOW, N	NSA Series,	SM Series						
6	USGV6 C	anahility e	ummary (For each (	distinct IPv6 stack in the product	provide a ou	mman, of the l	100 c and hills					
	summary	e a exa	mole-prod-id/stack-1: I	JSGv6-v1-Host: IPv6-Base+Addr	Provide a su Arch±lPego	mmary or its t	JSGv6 capabilities below and include a detailed test result					
		USG	6-v1-Router IPv6-Bas	se+Addr-Arch+SLAAC+DHCP-P	refix+DNS-	lient+IDv4+9	NMP+DS+APFW+Link= Ethernet					
				or real rion of the property	i Gila : Dito-	Mentil 4410	MAINLADO-WLLAAAFIIIK- EftiGLIIGE					
7	Self Conf	ained or (	Composite SDOC? (M	fust indicate one)								
'ES			6 capabilities of this product	The state of the s	canabilities of	his product are p	rayidad by the use and/or integration of smoothed account that have					
	are address		test results reported in this	their own unique USGv6	Some or all of the USGv6 capabilities of this product are provided by the use and/or integration of umodified components that have their own unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's							
	SDOC.			page 2 will indicate which	page 2 will indicate which capabilities are provided by specific referenced components (product-id/stack-id).							
8	Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).											
	Compone	ent Suppli	er	Product ID:	Stack ID:		lotes:					
[1]				1		The second second						
[2]												
[3]			Carried Total									
[4]							30.5 pr					
9	Supplem	Supplementary Attestations (Answer all).										
	Y This product is fully functional in dual stack environments. That is, no claimed					This product is	fully functional in IPv6 only environments. That is, no claimed capabilities					
		Capabilities	are invalidated ifthis product	is operated in a dual stack (6 and		are invalidated if this product is deployed in a network environment that does not supp						
_	4)network environment.  This SDOC contains a complifities test report for each unique ID-6 stock in the					lpv4.						
	This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If not, the stacks/ports not covered are documented, and how their Ipv6 capabilities differ from those reported are explained.					All of the produ	cts listed in the product family in section 5 are implemented such that pabilities are identical in form and function across the entire product					
						family. The specific conformance and interoperability test results for the USGv6						
						capabilities of a	in identified member of this product family are provided in this SDOC.					
		g.,				The SDOC atte	sts that these tested USGv6 capabilitiesare identical and unmodified for					
10	Signature		1		Date	all the products						
						12-6-	201					
	Print Name	e / Title	USHA SANI	AGALA, Senior Prog	M	2						
e inst	ructions for fiel	de 1-12 on P	ana 4	racing prof	ram F	anager						

		liers Declaration of Conformity for USGV			and the same of the same of					3v6-v1 SDOC-v1.10 Page		
Product Id:		SonicOS	Stack Id:						6.5			
Salam I			Context /	Suppo	rted Capa	abilities		USGv6 Testing P	rogram Results	Annual State Control of the Control		
Spec /			Configuration		1000		Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #.		
Reference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref		
P500-267	6.1	IPv6 Basic Requirements										
	_	support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base		- 2	7	Basic v1.* C	UNH-IOL/26833	Basic_V1.*_I	UNH-IOL/26835		
_	-	support of PMTU Discovery Protocol requirements	PMTU SLAAC		Р		Basic_v1.*_C	UNH-IOL/26833	Basic_V1.* I	UNH-IOL/26835		
	_	support of stateless address auto-configuration support of Creation of Global Addresses			P		SLAAC-V1.* C	UNH-IOL/26834	SLAAC-V1.*	UNH-IOL/26836		
	_	support of Cleanor of Global Addresses support of SLAAC privacy extensions.	SLAAC - c(M) PrivAddr		Р		SLAAC-V1.*_C	UNH-IOL/26834	SLAAC-V1.*_I	UNH-IOL/26836		
		support of stateful (DHCP) address auto-					Self Test DHCP Client v1.* C		Self Test			
		support of state of Children autorists auto-	DHCP-Prefix		Р		Self Test	Self Declaration	DHCP_Client_v1.*_t Self Test			
		Support of neighbor discovery security extensions	SEND				Self Test	Self Deciaration	Self Test	Self Declaration		
2500-267	6.6	Addressing Requirements	CENT				Sen Test		2011 1021			
		support of addressing architecture regts	Addr-Arch		-		Addr_Arch_v1.* C	UNH-IOL/26837	Addr_Arch_v1.*_[	UNH-IOL/26838		
		support of cryptographically generated addresses	CGA				Self Test	UNIT-10C/20037	Self Test	UNIT-10L/26838		
P500-267	6.7	IP Security Requirements	OGN		Toronto and		Sen rest		38H 18SI			
		support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C	1.00	IPsecv3_v1,*_i			
		support for automated key management					IKEv2_v1.* C		IKEv2_v2.*_I			
- 3		support for encapsulating security payloads in IP					ESPv3_v1.*_C		ESP_v1.*_I			
P500-267	6.11	Application Requirements		200000		( S						
1		support of DNS client/resolver functions	DNS-Client		₽	-	Self Test	Self Declaration	Self Test	Self Declaration		
	-55.55	support of Socket application program interfaces	SOCK	5	a una	A State of	Self Test	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Self Test	Ban Bana anon		
		support of IPv6 uniform resource Identifiers	URI	-	-		Self Test		Self Test			
		support of a DNS server application	DNS-Server	2			Self Test		Self Test			
4.00	44	support of a DHCP server application	DHCP-Server	2	11-12-	800	Self Test	Self Declaration	DHCP_Serv_v1.*_I			
P500-267	6.2	Routing Protocol Requirements		1								
mind-find.		support of the intra-domain (interior) routing	IGW	The same of			Self Test	Self Declaration	OSPFv3_v1.*_I			
		support for inter-domain (exterior) routing protocols	EGW	Attendance			Self Test	Self Declaration	BGP_v1.*_I			
P500-267	6.4	Transition Mechanism Requirements		District of the last				Service Control of the Control of th				
		support of interoperation with IPv4-only systems	IPv4		Р		Self Test	Self Declaration	Self Test	Self Declaration		
P500-267	0.0	support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test	Carlos Ca		
P300-207	6.8	Network Management Requirements	CNIME	4000000					Self Test			
P500-267	6.9	support of network management services Multicast Regulrements	SNMP	F-12-7-123			Self Test	Self Declaration	Self Test	Self Declaration		
F 300-201	0.5	support of basic multicast	Mcast				0-47-4	0-1/0-1-1/0-1		The second second		
		full support of multicast communications	SSM	_			Self Test	Self Declaration	0.47			
P500-267	6.10	Mobility Requirements	JOM	-			Self Test		Self Test			
		support of mobile IP capability.	MIP				Self Test		Self Test			
	10000	support of mobile network capabilities	NEMO	A Principal of		9	Self Test		Self Test			
P500-267	6.3	Quality of Service Requirements	Assertation of the	2 0	1	1	1007 1001		Gen resi			
		support of Differentiated Services capabilities	DS		100		Self Test	Self Declaration	Self Test	Self Declaration		
P500-267	6.12	Network Protection Device Requirements	Later Control of the			The State of the S	Total Total	Con a Contaction	Och 103t	OBII Deciaration		
		support of common NPD regts	NPD		A		N1JN2JN3JN4_v1.3					
		support of basic firewall capabilities	FW	2500	Shootid		N1 FW v1.3					
		support of application firewall capabilities	APFW	SHEET, 1993	SIP.		Self Test	Self Declaration		Self Declaration		
2000		support of intrusion detection capabilities	IDS		200	9000	N3_IDS_v1.3			Con Docidianon		
		support of intrusion protection capabilities	IPS	(C-1000)	Contraction.	9	N4_IPS_v1.3		Note: No			
P500-267	6.5	Link Specific Technologies								Separation - Have been		
		support of robust packet compression services	ROHC				Self Test		Self Test	Access of the same		
	_	support of link technology (O:1)	Link= Ethernet	-		9	Self Test	Self Declaration	Self Test	Self Declaration		
		Import on monday)	1 124									
	-	(repeat as needed) support of link technology	riuk=				A Commence of the Commence of	THE RESERVE OF THE PARTY OF THE				
12		< Check HERE if this stack's DOC Included	ies additional	inform	ation at	out tes	ted capabilities and	options on an attached pag	e 3 of notes.			
		support for USGv6-v1 Requirements for capabili	ity.			Color						
		Blank - SDOC makes no declaration for this capability.				9	Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.					
		assed required tests of USGv6-V1 requirements for these capabilities,				E 2	Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.					
N	See not	ee notes page for details on the level of support of USGv6-v1 reequirements for this capability.				Indicates capability that is left optional / ocnditional by the recommedations of the USGy6-v1 Profile.						
		capability not supported in product.								O-VVI FORG.		
st Suite -	Specific	USGv6 Test suite used for test. See: http://www.anto	I.nist.gov/usgv6/te	6/test-specifications.html			Note # - reference to a detailed note about this capability or result on attached page					
and I ale t D	egult ID	ult ID - Abbreviation of accredited laboratory and its local identifier for this test result.					Component Ref	- Supplier / Product / Stack ID of dist	inctly tested component t	hat provides this canability		
St Lab / K	COULT IN											

DECIME AND EDIOC AND ADDRESS OF

Gene aims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overa vork protection are given on Page 2. Detailed instructions for completing and interpreting each numb gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

rall results	document describes network product from the identified supplier that claims sup of testing USGv6 capabilities for conformance, interoperability and network prot are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv	te
Fleid	Description and Instructions	
<sub>27</sub> 1	The Document Requiring Conformity: Identifies the profile version implemented. Not a user completable field.	
2	Product Identifier: Supplier's concise name for the product declared.	
3	Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.	
4	Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).	
5	Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.	
6	USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).	
7	Self Contained or Composite SDOC: If this SDOC relies on the test results	

- . For
- esults of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager. dated. Printed name and position title on the line below.

## Fleid **Description and Instructions**

11 Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product ld and Stack ld labels. Product ld is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked Self Test have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.

Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.

Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.