	SUPP		CT IN	NFORMATION	SIGNATURE		
SUPP		Super Micro Computer, I	nc.				
SUPP	LIER CONTACT EMAIL			WIU 9U will yu (May 23, 2024 10:21 PDT)			
	ACCREDITED L	ABORATORY		ACCREDITED LABO	RATORY SIGN	ATURE	
LABO	RATORY NAME		tory				
LABO	RATORY CONTACT EMAIL	usav6-sdoc@iol.unh.e	du	Michayla Newcore Michayla Newcombe (May 23, 2024 1	1100 5:45 EDT)		
	[2] PRODUCT VE				DUCT ID		
F٧	V 4.40 / D	river 1.13.	7	AOC-S1	00GC [.]	-i2C	
			DUC			55	
	APPLICABLE SER	RIES HARDWARE		APPLICABLE SE	ERIES SOFTWA	ARE	
		• •	R CO	OMPOSITE SDOC			
	hitary : All of the declared ca ssed by original test results	apabilities of this product are reported in this SDoC.		Composite: Some or all of are provided by the use and/or components that have their ow relevant referenced SDoCs are linked.	integration of unr n unique SDoCs.	nodified All of the	
[6] REF	SUPPLIER	PRODUCT ID/STACK ID		CAPABILITY SUMMA	ARY	COMPOSITE SDOC LINK	
i.	Super Micro Computer, Inc.		USC	Gv6-r1:Host+IPv6-Only+Core+SLAAC+Ad	dr-Arch+Link=Ethernet		
		[7] USGV6-CAP		EREQUIREMENTS			
Ου	SGv6-r1-Capable-Host	USGv6-r1-Capable-Route		USGv6-r1-Capable-Switch	USGv6-r1-Ca	able-NPP	
			(S) F	REFERENCED	-		
i.	NIST SP 500-267Br1, U	ISGv6 Profile					
ii.		[9] SUPPLEMEN	TAR	RY ATTESTATIONS			
	his product is fully functiona				nal in IPv6 only e	nvironments	
This product is fully functional in dual stack environments. That is, no claimed capabilities are invalidated if this product is operated in a dual stack (IPv6 and IPv4) network environment.							
uniqu cover	his SDoC contains a capabi e IPv6 stack in the product. ed are documented, and ho hose reported are explained	If not, the stacks/ports not w their IPv6 capabilities diffe	r	All of the products listed in the product family in section 4 are implemented such that their capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the capabilities of an identified member of this product family are provided in this SDoC. The SDoC attests that these tested capabilities are identical and unmodified for all the products cited above.			

Host Capabilities

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY
[11]	CAPABILITY	CONFO	RMANCE	INTEROPERABIL	ITY/FUNCTIONAL	NOTES
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	
PASS	IPv6-ONLY			IPv6- ONLY_R1v1.*_F	UNH-IOL/38208	
PASS	Core	Core_R1v1.*_C	UNH-IOL/38204	Core_R1v1.*_I	UNH-IOL/38206	
-	Extended-ICMP	Self-Test		Self-Test		
-	PLPMTUD	Self-Test		Self-Test		
-	ND-Ext	Self-Test		Self-Test		
-	ND-WL	Self-Test		Self-Test		
-	SEND	Self-Test		Self-Test		
PASS	SLAAC	SLAAC_R1v1.*_C	UNH-IOL/38204	SLAAC_R1v1.*_I	UNH-IOL/38206	
-	PriAddr	Self-Test		Self-Test		
-	DHCP- Stateless	DHCP- Stateless_R1v1 _*_C		DHCP- Stateless_R1v1 .*_I		
-	DHCP-Client	DHCP- Client_R1v1.*_C		DHCP- Client_R1v1.*_I		
-	DHCP-Client- Ext	Self-Test		Self-Test		
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I		
-	DHCP-Prefix- Ext	Self-Test		Self-Test		
-	6Lo	Self-Test		Self-Test		

Host Capabilities

	Hanna Frank - Ha	Self-Test		Self-Test	
-	Happy-Eyeballs				
PASS	Addr-Arch	Addr- Arch_R1v1.*_C	UNH-IOL/38205		UNH-IOL/38207
-	CGA	Self-Test		Self-Test	
-	DNS-Client	Self-Test		Self-Test	
-	URI	Self-Test		Self-Test	
-	NTP-Client	Self-Test		Self-Test	
-	NTP-Server	Self-Test		Self-Test	
-	DNS-Server	Self-Test		Self-Test	
-	DHCP-Server	DHCP- Server_R1v1.*_C		DHCP- Server_R1v1.*_I	
-	DHCP-Server- Ext	Self-Test		Self-Test	
-	DHCP-Relay	DHCP- Relay_R1v1.*_C		DHCP- Relay_R1v1.*_I	
-	IPsec	IPsec_R1v1.*_C		IPsec_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C		IPsec-SHA- 512_R1v1.*_I	
-	SSHV2	Self-Test		Self-Test	
-	TLS	Self-Test		Self-Test	
-	TLS-1.3	Self-Test		Self-Test	
-	Tunneling-IP	Self-Test		Self-Test	

Host Capabilities

-	Tunneling-UDP	Self-Test		Self-Test		
-	XLAT	Self-Test		Self-Test		
-	NAT64	Self-Test		Self-Test		
-	DNS64	Self-Test		Self-Test		
-	SNMP	Self-Test		Self-Test		
-	Tunneling	Self-Test		Self-Test		
-	DiffServ	Self-Test		Self-Test		
-	NETCONF	Self-Test		Self-Test		
-	SSM	Self-Test		Self-Test		
-	Multicast	Multicast_R1v1 .*_C		Multicast_R1v1 .*_I		
-	ECN	Self-Test		Self-Test		
PASS	Link = Ethernet	Self-Test	Self Declaration	Self-Test	Self Declaration	

Router Capabilities

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY
[11] SUPPORTED		CONFOR	MANCE RESULT ID	INTEROPERABIL TEST	ITY/FUNCTIONAL RESULT ID	NOTES
CAPABILITY	CAPABILITY	SELECTION	RESULTID	SELECTION	RESULTID	
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F		
-	Core	Core_R1v1.*_C		Core_R1v1.*_I		
-	Extended-ICMP	Self-Test		Self-Test		
-	PLPMTUD	Self-Test		Self-Test		
-	ND-Ext	Self-Test		Self-Test		
-	ND-WL	Self-Test		Self-Test		
-	SEND	Self-Test		Self-Test		
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I		
-	PrivAddr	Self-Test		Self-Test		
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I		
-	DHCP-Prefix- Ext	Self-Test		Self-Test		
-	6Lo	Self-Test		Self-Test		
-	Addr-Arch	Addr- Arch_R1v1.*_C		Addr- Arch_R1v1.*_I		
-	CGA	Self-Test		Self-Test		

Router Capabilities

			0. If T		
-	DNS-Client	Self-Test	Self-Test		
-	URI	Self-Test	Self-Test		
-	NTP-Client	Self-Test	Self-Test		
-	NTP-Server	Self-Test	Self-Test		
-	DNS-Server	Self-Test	Self-Test		
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_		
-	DHCP-Server- Ext	Self-Test	Self-Test		
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_		
-	OSPF	Self-Test	OSPF_R1v1.*_		
-	OSPF-IPsec	Self-Test	Self-Test		
-	OSPF-Auth	Self-Test	OSPF- Auth_R1v1.*_I	,	
-	OSPF-Ext	Self-Test	Self-Test		
-	OSPF-Trans	Self-Test	Self-Test		
-	OSPF-Graceful	Self-Test	Self-Test		
-	ISIS	Self-Test	Self-Test		
-	IS-IS-Auth	Self-Test	Self-Test		
-	IS-IS-Ext	Self-Test	Self-Test		
-	IS-IS-MT	Self-Test	Self-Test		

		Self-Test	BGP_R1v1.*_I	
-	BGP			
-	BGP-Reflect	Self-Test	Self-Test	
-	BGP-Graceful	Self-Test	Self-Test	
-	BGP-FlowSpec	Self-Test	Self-Test	
-	BGP-OV	Self-Test	Self-Test	
-	BGP-VPLS	Self-Test	Self-Test	
-	BGP-EVPN	Self-Test	Self-Test	
-	BGP-6VPE	Self-Test	Self-Test	
-	BGP-MVPN	Self-Test	Self-Test	
-	MPLS	Self-Test	Self-Test	
-	CE-Router	CE_Router_R1v 1.*_C	CE_Router_R1v 1.*_I	
-	VRRP	Self-Test	Self-Test	
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I	
-	IPsec-VPN	IPsec- VPN_R1v1.*_C	IPsec- VPN_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I	
-	IPsec-SHA-512- VPN	IPsec-SHA-512- VPN_R1v1.*_C	IPsec-SHA-512- VPN_R1v1.*_I	
-	SSHV2	Self-Test	Self-Test	
-	TLS	Self-Test	Self-Test	

	1			
-	TLS-1.3	Self-Test	Self-Test	
-	Tunneling-IP	Self-Test	Self-Test	
-	Tunneling-UDP	Self-Test	Self-Test	
-	GRE	Self-Test	Self-Test	
-	DS-Lite	Self-Test	Self-Test	
-	LW4over6	Self-Test	Self-Test	
-	MAP-E	Self-Test	Self-Test	
-	MAP-T	Self-Test	Self-Test	
-	XLAT	Self-Test	Self-Test	
-	NAT64	Self-Test	Self-Test	
-	DNS64	Self-Test	Self-Test	
-	6PE	Self-Test	Self-Test	
-	LISP	Self-Test	Self-Test	
-	SNMP	Self-Test	Self-Test	
-	Tunneling	Self-Test	Self-Test	
-	DiffServ	Self-Test	Self-Test	
-	NETCONF	Self-Test	Self-Test	
-	SSM	Self-Test	Self-Test	

Router Capabilities

-	PIM-SM	Self-Test	Self-Test	
-	PIM-SM-IPsec	Self-Test	Self-Test	
-	PIM-SM-BiDir	Self-Test	Self-Test	
-	Multicast	Multicast_R1v1. *_C	Multicast_R1v1. *_I	
-	ECN	Self-Test	Self-Test	
-	Link =	Self-Test	Self-Test	

Application Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFO TEST SELECTION	RMANCE RESULT ID	INTEROPERABIL TEST SELECTION	ITY/FUNCTIONAL RESULT ID	NOTES	
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	App-Serv=			APP- ONLY_R1v1.*_F			
-	Link =			Self-Test			

NPP Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILI	TY/FUNCTIONAL	NOTES	
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	FW	FW_R1v1.*_C					
-	APFW	Self-Test					
-	IDS	FW_R1v1.*_C					
-	IPS	FW_R1v1.*_C					
-	Link =	Self-Test					

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILIT	Y/FUNCTIONAL			
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	NOTES		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	DHCPv6-Guard	Self-Test		Self-Test				
-	RA-Guard	Self-Test		Self-Test				
-	MLD-Snooping	Self-Test		Self-Test				
-	Link =	Self-Test		Self-Test				

1	CONTACT INFORMATION	Supplier name, email and signature (digital recommended). Include printed name and date if wet ink signed. Accredited laboratory name, email and signature (digital recommended). Include printed name and date if wet ink signed.
2	PRODUCT VERSION TESTED	Firmware/ software version of product declared
3	PRODUCT ID	Suppliers concise name for product declared
4	PRODUCT FAMILY	Applicable hardware or software with an unmodified IPv6 stack from "PRODUCT VERSION TESTED"
5	UNITARY OR COMPOSITE	Indicate if this is a unitary or composite SDoC. If composite is checked, composite SDoC must be linked in section 6.
6	REF	Reference number to profile(s) reference in this SDoC
	SUPPLIER	Supplier name
	PRODUCT ID/STACK ID	Product ID must match field 3. As there may be more than one unique IPv6 stack, stack ID identifies particular stack described in CAPABILITY SUMMARY. Each unique stack requires a CAPABILTY SUMMARY.
	CAPABILITY SUMMARY	The strong notation as described in NIST-SP-500-267Ar1 that describes the product capabilities of the given stack.
	COMPOSITE SDOC LINK	URL link to composite SDoC referenced.
7	USGV6-CAPABLE REQUIREMENTS	Refer to section 5 in NIST-SP-500-267Br1 for CSS strings referenced in this section. Check the appropriate box if the product meets the requirements.
8	PROFILE(S) REFERENCED	Profile(s) referenced in the SDoC.
9	SUPPLEMENTARY ATTESTATIONS	Attestations made by the supplier. Check all that apply.
10	PRODUCT ID/STACK ID	PRODUCT ID/STACK ID for stack documented on given page.
	CAPABILITY SUMMARY	CAPABILITY SUMMARY for stack documented on given page.
11	SUPPORTED CAPABILITY	"PASS" – All requirements of the capability have been met
		"NOTES" – See notes for details regarding the level of support for this capability
		"X" – Capability not supported
		BLANK – No declaration for this capability
	CAPABILITY	IPv6 Capability as described in NIST-SP-500-267Ar1.
	TEST SELECTION	Test Selection Tables version of capabilities with existing test programs. Capabilities without an existing test program are indicated with "Self-Test"
	RESULT ID	Abbreviation of accredited laboratory and unique identifier of test result. Capabilities with "Self-Test" can be self-declared writing "Self Declaration" in the cell.
	NOTES	The cell must be filled out if "NOTE" is indicated for SUPPORTED CAPABILITY. Suppliers may use notes to clarify unsupported features or non-passing results.

SUPPLIER GENERAL NOTES