		[1] CONTACT	INFORMATION			
	SUPP		SUPPLIER	SIGNATURE		
SUPPL		Cisco Systems Inc.	– Ashlee Panburan	a		
SUPPL	IER CONTACT EMAIL	ascummin@cisco.com	Ashlee Panburana (Nov 12, 2024 13:3	7 EST)		
	ACCREDITED L	ABORATORY	ACCREDITED LABOR	RATORY SIGN	ATURE	
LABO	RATORY NAME	UNH InterOperability Laborator	Michayla Newcon	uhe		
LABO	RATORY CONTACT EMAIL	usgv6-sdoc@iol.unh.edu	Michayla Newcombe (Nov 12, 2024 15	5:11 EST)		
	[2] PRODUCT VE	RSION TESTED	[3] PRO	DUCT ID		
	IOS XE	17.15.1	C950	0-16X		
		[4] PROD	JCT FAMILY			
	APPLICABLE SER	IES HARDWARE	APPLICABLE SE	RIES SOFTWA	RE	
			COMPOSITE SDOC			
	i itary : All of the declared ca ssed by original test results	apabilities of this product are reported in this SDoC.	Composite: Some or all of are provided by the use and/or components that have their own relevant referenced SDoCs are linked.	integration of unn n unique SDoCs.	nodified All of the	
[6] REF	SUPPLIER	PRODUCT ID/STACK ID	CAPABILITY SUMMA	RY	COMPOSITE SDOC LINK	
i.	Cisco Systems Inc.	t	JSGv6-r1:Router+Core+SLAAC+Addr-Arch+OSPF+O	SPF-Auth+Link=Ethernet		
		[7] USGV6-CAPAB	LE REQUIREMENTS			
	SGv6-r1-Capable-Host		USGv6-r1-Capable-Switch	USGv6-r1-Cap	able-NPP	
-) REFERENCED			
i.	NIST SP 500-267Br1, U	SGv6 Profile				
ii.		[9] SI IPPLEMENT	ARY ATTESTATIONS			
	ais product is fully functions	l in dual stack environments.		al in IPv6 only or	vironmento	
That is	s, no claimed capabilities ar	re invalidated if this product is d IPv4) network environment.	This product is fully function That is, no claimed capabilities a deployed in a network environm	are invalidated if t	his product is	
unique covere	nis SDoC contains a capabi e IPv6 stack in the product. ed are documented, and ho hose reported are explained	If not, the stacks/ports not w their IPv6 capabilities differ	All of the products listed in the product family in section 4 are implemented such that their capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the capabilities of an identified member of this product family are provided in this SDoC. The SDoC attests that these tested capabilities are identical and unmodified for all the products cited above.			

Host Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY				
[11] SUPPORTED	CAPABILITY	CONFOR		INTEROPERABILI		NOTES			
CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID				
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F					
-	Core	Core_R1v1.*_C		Core_R1v1.*_I					
-	Extended-ICMP	Self-Test		Self-Test					
-	PLPMTUD	Self-Test		Self-Test					
-	ND-Ext	Self-Test		Self-Test					
-	ND-WL	Self-Test		Self-Test					
-	SEND	Self-Test		Self-Test					
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I					
-	PriAddr	Self-Test		Self-Test					
-	DHCP- Stateless	DHCP- Stateless_R1v1 .*_C		DHCP- Stateless_R1v1 _*_I					
-	DHCP-Client	DHCP- Client_R1v1.*_C		DHCP- Client_R1v1.*_I					
-	DHCP-Client- Ext	Self-Test		Self-Test					
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I					
-	DHCP-Prefix- Ext	Self-Test		Self-Test					
-	6Lo	Self-Test		Self-Test					

Host Capabilities

		Self-Test	Self-Test		
-	Happy-Eyeballs	Sen-rest	- Sen-Test		
-	Addr-Arch	Addr- Arch_R1v1.*_C	Addr- Arch_R1v1.*_I		
-	CGA	Self-Test	Self-Test		
-	DNS-Client	Self-Test	Self-Test		
-	URI	Self-Test	Self-Test		
-	NTP-Client	Self-Test	Self-Test		
-	NTP-Server	Self-Test	Self-Test		
-	DNS-Server	Self-Test	Self-Test		
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I		
-	DHCP-Server- Ext	Self-Test	Self-Test		
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I		
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I		
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I		
-	SSHV2	Self-Test	Self-Test		
-	TLS	Self-Test	Self-Test		
-	TLS-1.3	Self-Test	Self-Test		
-	Tunneling-IP	Self-Test	Self-Test		

Host Capabilities

		Self-Test	Self-Test		
-	Tunneling-UDP				
-	XLAT	Self-Test	Self-Test		
-	NAT64	Self-Test	Self-Test		
-	DNS64	Self-Test	Self-Test		
-	SNMP	Self-Test	Self-Test		
-	Tunneling	Self-Test	Self-Test		
-	DiffServ	Self-Test	Self-Test		
-	NETCONF	Self-Test	Self-Test		
-	SSM	Self-Test	Self-Test		
-	Multicast	Multicast_R1v1 .*_C	Multicast_R1v1 .*_I		
-	ECN	Self-Test	Self-Test		
-	Link =	Self-Test	Self-Test		

Router Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY			
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFOF TEST SELECTION	RMANCE RESULT ID	INTEROPERABIL TEST SELECTION	ITY/FUNCTIONAL RESULT ID	NOTES		
NOTES	IPv6-ONLY			IPv6- ONLY_R1v1.*_F	UNH-IOL/38899			
PASS	Core	Core_R1v1.*_C	UNH-IOL/38894	Core_R1v1.*_I	UNH-IOL/38896			
-	Extended-ICMP	Self-Test		Self-Test				
-	PLPMTUD	Self-Test		Self-Test				
-	ND-Ext	Self-Test		Self-Test				
-	ND-WL	Self-Test		Self-Test				
-	SEND	Self-Test		Self-Test				
PASS	SLAAC	SLAAC_R1v1.*_C	UNH-IOL/38894	SLAAC_R1v1.*_I	UNH-IOL/38896			
-	PrivAddr	Self-Test		Self-Test				
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I				
-	DHCP-Prefix- Ext	Self-Test		Self-Test				
-	6Lo	Self-Test		Self-Test				
PASS	Addr-Arch	Addr- Arch_R1v1.*_C	UNH-IOL/38895	Addr- Arch_R1v1.*_I	UNH-IOL/38897			
-	CGA	Self-Test		Self-Test				

Router Capabilities

		Salf Taat	Calf Test		
-	DNS-Client	Self-Test	Self-Test		
-	URI	Self-Test	Self-Test		
-	NTP-Client	Self-Test	Self-Test		
-	NTP-Server	Self-Test	Self-Test		
	DNS-Server	Self-Test	Self-Test		
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I		
-	DHCP-Server- Ext	Self-Test	Self-Test		
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I		
PASS	OSPF	Self-Test	OSPF_R1v1.*_I	UNH-IOL/38898	
-	OSPF-IPsec	Self-Test	Self-Test		
PASS	OSPF-Auth	Self-Test	OSPF- Auth_R1v1.*_I	UNH-IOL/38898	
	OSPF-Ext	Self-Test	Self-Test		
	OSPF-Trans	Self-Test	Self-Test		
	OSPF-Graceful	Self-Test	Self-Test		
	ISIS	Self-Test	Self-Test		
	IS-IS-Auth	Self-Test	Self-Test		
-	IS-IS-Ext	Self-Test	Self-Test		
-	IS-IS-MT	Self-Test	Self-Test		

		Self-Test	BGP_R1v1.*_I	
-	BGP			
-	BGP-Reflect	Self-Test	Self-Test	
-	BGP-Graceful	Self-Test	Self-Test	
-	BGP-FlowSpec	Self-Test	Self-Test	
-	BGP-OV	Self-Test	Self-Test	
-	BGP-VPLS	Self-Test	Self-Test	
-	BGP-EVPN	Self-Test	Self-Test	
-	BGP-6VPE	Self-Test	Self-Test	
-	BGP-MVPN	Self-Test	Self-Test	
-	MPLS	Self-Test	Self-Test	
-	CE-Router	CE_Router_R1v 1.*_C	CE_Router_R1v 1.*_I	
-	VRRP	Self-Test	Self-Test	
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I	
-	IPsec-VPN	IPsec- VPN_R1v1.*_C	IPsec- VPN_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I	
-	IPsec-SHA-512- VPN	IPsec-SHA-512- VPN_R1v1.*_C	IPsec-SHA-512- VPN_R1v1.*_I	
-	SSHV2	Self-Test	Self-Test	
-	TLS	Self-Test	Self-Test	

	1			
-	TLS-1.3	Self-Test	Self-Test	
-	Tunneling-IP	Self-Test	Self-Test	
-	Tunneling-UDP	Self-Test	Self-Test	
-	GRE	Self-Test	Self-Test	
-	DS-Lite	Self-Test	Self-Test	
-	LW4over6	Self-Test	Self-Test	
-	MAP-E	Self-Test	Self-Test	
-	MAP-T	Self-Test	Self-Test	
-	XLAT	Self-Test	Self-Test	
-	NAT64	Self-Test	Self-Test	
-	DNS64	Self-Test	Self-Test	
-	6PE	Self-Test	Self-Test	
-	LISP	Self-Test	Self-Test	
-	SNMP	Self-Test	Self-Test	
-	Tunneling	Self-Test	Self-Test	
-	DiffServ	Self-Test	Self-Test	
-	NETCONF	Self-Test	Self-Test	
-	SSM	Self-Test	Self-Test	

Router Capabilities

-	PIM-SM	Self-Test		Self-Test		
-	PIM-SM-IPsec	Self-Test		Self-Test		
-	PIM-SM-BiDir	Self-Test		Self-Test		
-	Multicast	Multicast_R1v1. *_C		Multicast_R1v1. *_I		
-	ECN	Self-Test		Self-Test		
PASS	Link = Ethernet	Self-Test	Self Declaration	Self-Test	Self Declaration	

Application Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY			
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFO TEST SELECTION	RMANCE RESULT ID	INTEROPERABIL TEST SELECTION	ITY/FUNCTIONAL RESULT ID	NOTES		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	App-Serv=			APP- ONLY_R1v1.*_F				
-	Link =			Self-Test				

NPP Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY			
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILI	TY/FUNCTIONAL	NOTES		
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID			
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	FW	FW_R1v1.*_C						
-	APFW	Self-Test						
-	IDS	FW_R1v1.*_C						
-	IPS	FW_R1v1.*_C						
-	Link =	Self-Test						

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILIT	Y/FUNCTIONAL			
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	NOTES		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	DHCPv6-Guard	Self-Test		Self-Test				
-	RA-Guard	Self-Test		Self-Test				
-	MLD-Snooping	Self-Test		Self-Test				
-	Link =	Self-Test		Self-Test				

1	CONTACT INFORMATION	Supplier name, email and signature (digital recommended). Include printed name and date if wet ink signed. Accredited laboratory name, email and signature (digital recommended). Include printed name and date if wet ink signed.
2	PRODUCT VERSION TESTED	Firmware/ software version of product declared
3	PRODUCT ID	Suppliers concise name for product declared
4	PRODUCT FAMILY	Applicable hardware or software with an unmodified IPv6 stack from "PRODUCT VERSION TESTED"
5	UNITARY OR COMPOSITE	Indicate if this is a unitary or composite SDoC. If composite is checked, composite SDoC must be linked in section 6.
6	REF	Reference number to profile(s) reference in this SDoC
	SUPPLIER	Supplier name
	PRODUCT ID/STACK ID	Product ID must match field 3. As there may be more than one unique IPv6 stack, stack ID identifies particular stack described in CAPABILITY SUMMARY. Each unique stack requires a CAPABILTY SUMMARY.
	CAPABILITY SUMMARY	The strong notation as described in NIST-SP-500-267Ar1 that describes the product capabilities of the given stack.
	COMPOSITE SDOC LINK	URL link to composite SDoC referenced.
7	USGV6-CAPABLE REQUIREMENTS	Refer to section 5 in NIST-SP-500-267Br1 for CSS strings referenced in this section. Check the appropriate box if the product meets the requirements.
8	PROFILE(S) REFERENCED	Profile(s) referenced in the SDoC.
9	SUPPLEMENTARY ATTESTATIONS	Attestations made by the supplier. Check all that apply.
10	PRODUCT ID/STACK ID	PRODUCT ID/STACK ID for stack documented on given page.
	CAPABILITY SUMMARY	CAPABILITY SUMMARY for stack documented on given page.
11	SUPPORTED CAPABILITY	"PASS" – All requirements of the capability have been met
		"NOTES" – See notes for details regarding the level of support for this capability
		"X" – Capability not supported
		BLANK – No declaration for this capability
	CAPABILITY	IPv6 Capability as described in NIST-SP-500-267Ar1.
	TEST SELECTION	Test Selection Tables version of capabilities with existing test programs. Capabilities without an existing test program are indicated with "Self-Test"
	RESULT ID	Abbreviation of accredited laboratory and unique identifier of test result. Capabilities with "Self-Test" can be self-declared writing "Self Declaration" in the cell.
	NOTES	The cell must be filled out if "NOTE" is indicated for SUPPORTED CAPABILITY. Suppliers may use notes to clarify unsupported features or non-passing results.

SUPPLIER GENERAL NOTES